

# Oracle9i Application Server

PL/SQL Web Toolkit Reference

Release 1.0.2.2

April 2001

Part No. A90101-01

**ORACLE®**



Oracle 9i Application Server

PL/SQL Web Toolkit Reference, Release 1.0.2.2

Part No. A90101-01

Copyright © 1996, 2001, Oracle Corporation. All rights reserved.

Primary Author: Sanjay Singh

Contributing Authors: Cheryl Smith, Catherine McAulay

Contributors: Sanjay Patil, Pushkar Kapasi

The Programs (which include both the software and documentation) contain proprietary information of Oracle Corporation; they are provided under a license agreement containing restrictions on use and disclosure and are also protected by copyright, patent, and other intellectual and industrial property laws. Reverse engineering, disassembly, or decompilation of the Programs is prohibited.

The information contained in this document is subject to change without notice. If you find any problems in the documentation, please report them to us in writing. Oracle Corporation does not warrant that this document is error free. Except as may be expressly permitted in your license agreement for these Programs, no part of these Programs may be reproduced or transmitted in any form or by any means, electronic or mechanical, for any purpose, without the express written permission of Oracle Corporation.

If the Programs are delivered to the U.S. Government or anyone licensing or using the programs on behalf of the U.S. Government, the following notice is applicable:

**Restricted Rights Notice** Programs delivered subject to the DOD FAR Supplement are "commercial computer software" and use, duplication, and disclosure of the Programs, including documentation, shall be subject to the licensing restrictions set forth in the applicable Oracle license agreement. Otherwise, Programs delivered subject to the Federal Acquisition Regulations are "restricted computer software" and use, duplication, and disclosure of the Programs shall be subject to the restrictions in FAR 52.227-19, Commercial Computer Software - Restricted Rights (June, 1987). Oracle Corporation, 500 Oracle Parkway, Redwood City, CA 94065.

The Programs are not intended for use in any nuclear, aviation, mass transit, medical, or other inherently dangerous applications. It shall be the licensee's responsibility to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of such applications if the Programs are used for such purposes, and Oracle Corporation disclaims liability for any damages caused by such use of the Programs.

Oracle is a registered trademark of Oracle Corporation. Other names may be trademarks of their respective owners.



---

---

# Contents

<b>Send Us Your Comments .....</b>	<b>iii</b>
<b>Preface.....</b>	<b>v</b>
<b>1 The http and htf Packages</b>	
1.1 Summary .....	1-2
1.2 http.address .....	1-6
1.3 http.anchor, http.anchor2 .....	1-6
1.4 http.appletopen, http.appletclose .....	1-7
1.5 http.area .....	1-8
1.6 http.base .....	1-9
1.7 http.basefont .....	1-10
1.8 http.bgsound .....	1-10
1.9 http.big .....	1-10
1.10 http.blockquoteOpen, http.blockquoteClose .....	1-11
1.11 http.bodyOpen, http.bodyClose .....	1-11
1.12 http.bold .....	1-12
1.13 http.center .....	1-12
1.14 http.centerOpen, http.centerClose .....	1-13
1.15 http.cite .....	1-13
1.16 http.code .....	1-14
1.17 http.comment .....	1-14
1.18 http.dfn .....	1-15
1.19 http.dirlistOpen, http.dirlistClose .....	1-15

1.20	http.div .....	1-15
1.21	http.dlistOpen, http.dlistClose .....	1-16
1.22	http.dlistDef .....	1-16
1.23	http.dlistTerm .....	1-17
1.24	http.download_file .....	1-17
1.25	http.get_download_files_list .....	1-18
1.26	http.emphasis, http.em .....	1-18
1.27	htf.escape_sc .....	1-19
1.28	htf.escape_url .....	1-19
1.29	http.fontOpen, http.fontClose .....	1-20
1.30	htf.format_cell .....	1-21
1.31	http.formCheckbox .....	1-21
1.32	http.formOpen, http.formClose .....	1-22
1.33	http.formFile .....	1-22
1.34	http.formHidden .....	1-23
1.35	http.formImage .....	1-23
1.36	http.formPassword .....	1-24
1.37	http.formRadio .....	1-25
1.38	http.formReset .....	1-26
1.39	http.formSelectOpen, http.formSelectClose .....	1-26
1.40	http.formSelectOption .....	1-27
1.41	http.formSubmit .....	1-28
1.42	http.formText .....	1-29
1.43	http.formTextarea, http.formTextarea2 .....	1-29
1.44	http.formTextareaOpen, http.formTextareaOpen2, http.formTextareaClose .....	1-30
1.45	http.frame .....	1-31
1.46	http.framesetOpen, http.framesetClose .....	1-32
1.47	http.headOpen, http.headClose .....	1-33
1.48	http.header .....	1-33
1.49	http.htmlOpen, http.htmlClose .....	1-34
1.50	http.img, http.img2 .....	1-35
1.51	http.isindex .....	1-36
1.52	http.italic .....	1-36
1.53	http.keyboard, http.kbd .....	1-36
1.54	http.line, http.hr .....	1-37

1.55	htp.linkRel .....	1-38
1.56	htp.linkRev .....	1-38
1.57	htp.listHeader .....	1-39
1.58	htp.listingOpen, htp.listingClose .....	1-39
1.59	htp.listItem .....	1-39
1.60	htp.mailto .....	1-40
1.61	htp.mapOpen, htp.mapClose .....	1-41
1.62	htp.menuListOpen, htp.menuListClose .....	1-41
1.63	htp.meta .....	1-42
1.64	htp.nl, htp.br.....	1-43
1.65	htp.nobr.....	1-43
1.66	htp.noframesOpen, htp.noframesClose .....	1-43
1.67	htp.olistOpen, htp.olistClose .....	1-44
1.68	htp.para, htp.paragraph .....	1-45
1.69	htp.param .....	1-45
1.70	htp.plaintext .....	1-46
1.71	htp.preOpen, htp.preClose .....	1-46
1.72	htp.print, htp.prn.....	1-47
1.73	htp.prints, htp.ps .....	1-48
1.74	htp.s .....	1-48
1.75	htp.sample .....	1-49
1.76	htp.script.....	1-49
1.77	htp.small .....	1-50
1.78	htp.strike .....	1-50
1.79	htp.strong.....	1-51
1.80	htp.style.....	1-51
1.81	htp.sub.....	1-52
1.82	htp.sup .....	1-52
1.83	htp.tableCaption .....	1-53
1.84	htp.tableData.....	1-53
1.85	htp.tableHeader .....	1-54
1.86	htp.tableOpen, htp.tableClose .....	1-55
1.87	htp.tableRowOpen, htp.tableRowClose.....	1-56
1.88	htp.teletype.....	1-57
1.89	htp.title .....	1-58

1.90	htp.ulistOpen, htp.ulistClose .....	1-58
1.91	htp.underline.....	1-59
1.92	htp.variable.....	1-59
1.93	htp.wbr.....	1-59

## 2 The owa\_cache Package

2.1	Summary.....	2-1
2.2	owa_cache.disable .....	2-1
2.3	owa_cache.set_expires .....	2-2
2.4	owa_cache.set_cache .....	2-2
2.5	owa_cache.set_not_modified.....	2-3
2.6	owa_cache.get_level.....	2-3
2.7	owa_cache.get_etag.....	2-3

## 3 The owa\_cookie Package

3.1	Summary.....	3-1
3.2	owa_cookie.cookie data type .....	3-1
3.3	owa_cookie.get function.....	3-2
3.4	owa_cookie.get_all procedure .....	3-2
3.5	owa_cookie.remove procedure.....	3-3
3.6	owa_cookie.send procedure.....	3-3

## 4 The owa\_image Package

4.1	Summary.....	4-1
4.2	owa_image.NULL_POINT package variable.....	4-1
4.3	owa_image.point data type.....	4-2
4.4	owa_image.get_x function .....	4-2
4.5	owa_image.get_y function .....	4-2

## 5 The owa\_opt\_lock Package

5.1	Summary.....	5-1
5.2	owa_opt_lock.vcArray data type .....	5-2
5.3	owa_opt_lock.checksum function.....	5-2
5.4	owa_opt_lock.get_rowid function .....	5-3



5.5	owa_opt_lock.store_values procedure.....	5-3
5.6	owa_opt_lock.verify_values function .....	5-4

## 6 The owa\_pattern Package

6.1	Subprograms.....	6-1
6.2	Regular Expressions.....	6-2
6.2.1	Wildcard Tokens .....	6-2
6.2.2	Quantifiers.....	6-3
6.2.3	Flags .....	6-3
6.3	owa_pattern.amatch function.....	6-3
6.4	owa_pattern.change function and procedure .....	6-5
6.5	owa_pattern.getpat procedure .....	6-7
6.6	owa_pattern.match function.....	6-8
6.7	owa_pattern.pattern data type .....	6-11

## 7 The owa\_sec Package

7.1	Summary .....	7-1
7.2	owa_sec.get_client_hostname function.....	7-1
7.3	owa_sec.get_client_ip function .....	7-2
7.4	owa_sec.get_password function .....	7-2
7.5	owa_sec.get_user_id function .....	7-3
7.6	owa_sec.set_authorization procedure.....	7-3
7.7	owa_sec.set_protection_realm procedure.....	7-4

## 8 The owa\_text Package

8.1	Summary .....	8-1
8.2	owa_text.add2multi procedure .....	8-1
8.3	owa_text.multi_line data type.....	8-2
8.4	owa_text.new_row_list.....	8-2
8.5	owa_text.print_multi procedure .....	8-3
8.6	owa_text.print_row_list procedure .....	8-3
8.7	owa_text.row_list data type.....	8-3
8.8	owa_text.stream2multi procedure.....	8-4
8.9	owa_text.vc_arr data type .....	8-4

## 9 The owa\_util Package

9.1	Summary.....	9-1
9.2	owa_util.bind_variables function.....	9-2
9.3	owa_util.calendarprint procedure.....	9-3
9.4	owa_util.cellsprint procedure.....	9-4
9.5	owa_util.choose_date procedure.....	9-6
9.6	owa_util.dateType data type.....	9-7
9.7	owa_util.get_cgi_env function.....	9-8
9.8	owa_util.get_owa_service_path function.....	9-8
9.9	owa_util.get_procedure function.....	9-8
9.10	owa_util.http_header_close procedure.....	9-9
9.11	owa_util.ident_arr data type.....	9-9
9.12	owa_util.ip_address data type.....	9-9
9.13	owa_util.listprint procedure.....	9-10
9.14	owa_util.mime_header procedure.....	9-11
9.15	owa_util.print_cgi_env procedure.....	9-12
9.16	owa_util.redirect_url procedure.....	9-12
9.17	owa_util.showpage procedure.....	9-13
9.18	owa_util.showsource procedure.....	9-14
9.19	owa_util.signature procedure.....	9-14
9.20	owa_util.status_line procedure.....	9-14
9.21	owa_util.tablePrint function.....	9-15
9.22	owa_util.todate function.....	9-20
9.23	owa_util.who_called_me procedure.....	9-20

## Index

---

---

# Send Us Your Comments

**PL/SQL Web Toolkit Reference, Release 1.0.2.2**

**Part No. A90101-01**

Oracle Corporation welcomes your comments and suggestions on the quality and usefulness of this document. Your input is an important part of the information used for revision.

- Did you find any errors?
- Is the information clearly presented?
- Do you need more information? If so, where?
- Are the examples correct? Do you need more examples?
- What features did you like most?

If you find any errors or have any other suggestions for improvement, please indicate the document title and part number, and the chapter, section, and page number (if available). Send comments to:

- [iasdocs\\_us@oracle.com](mailto:iasdocs_us@oracle.com)

If you would like a reply, please give your name, address, telephone number, and electronic mail address.

If you have problems with the software, please contact your local Oracle Support Services.



---

---

# Preface

## Intended Audience

This guide is a reference for the PL/SQL Web Toolkit for Oracle9i Application Server 1.0.2.2.

## Structure

The packages in the the PL/SQL Web Toolkit are described in the following chapters:

- Chapter 1 describes the htp and htf packages which generate HTML tags.
- Chapter 2 describes the owa\_cache package which contains functions and procedures that enable the PL/SQL Gateway cache.
- Chapter 3 describes the owa\_cookie package which contains subprograms that send and retrieve HTTP cookies from the client's browser.
- Chapter 4 describes the owa\_image package which is used when you have any image map whose destination links invoke the PL/SQL Gateway.
- Chapter 5 describes the owa\_lock package which contains subprograms that are used to implement database locking for PL/SQL Gateway.
- Chapter 6 describes the owa\_pattern package which locates text patterns within strings and replaces the matched string with another string.
- Chapter 7 describes the owa\_sec package which contains functions, procedures, and data types to implement security.
- Chapter 8 describes the owa\_text package which contains subprograms used by owa\_pattern for manipulating strings.

- Chapter 9 describes the owa\_util package which contains utility subprograms.

## Related Documents

For more information, see the following manuals:

Part Number	Title
A90099-01	Oracle9i Application Server, Using the PL/SQL Gateway
.A87353-01	Oracle9i Application Server - Overview

## Conventions

The following conventions are used in this manual:

Convention	Meaning
. . .	Vertical ellipsis points in an example mean that information not directly related to the example has been omitted.
...	Horizontal ellipsis points in statements or commands mean that parts of the statement or command not directly related to the example have been omitted
<b>boldface text</b>	Boldface type in text indicates a term defined in the text, the glossary, or in both locations.
< >	Angle brackets enclose user-supplied names.
[ ]	Brackets enclose optional clauses from which you can choose one or none.

---

---

## The htp and htf Packages

The htp (hypertext procedures) and htf (hypertext functions) packages generate HTML tags. For instance, the htp.anchor procedure generates the HTML anchor tag, <A>. The following commands generate a simple HTML document:

```
create or replace procedure hello AS
BEGIN
    htp.htmlopen;           -- generates <HTML>
    htp.headopen;          -- generates <HEAD>
    htp.title('Hello');    -- generates <TITLE>Hello</TITLE>
    htp.headclose;         -- generates </HEAD>
    htp.bodyopen;          -- generates <BODY>
    htp.header(1, 'Hello'); -- generates <H1>Hello</H1>
    htp.bodyclose;         -- generates </BODY>
    htp.htmlclose;         -- generates </HTML>
END;
```

For every htp procedure that generates HTML tags, there is a corresponding htf function with identical parameters. The function versions do not directly generate output in your web page. Instead, they pass their output as return values to the statements that invoked them. Use these functions when you need to nest calls. To look up htf functions, see the entry for the corresponding htp procedures.

To print the output of htf functions, call the functions from within the htp.print procedure. It then prints its parameters to the generated web page.

---

---

**Note:** If you use values of the LONG data type in procedures such as htp.print, htp.prn, htp.prints, htp.pa or owa\_util.cellsprint, only the first 32 K of the LONG data is used. The LONG data is bound to a varchar2 data type in the procedure or function.

---

---

## 1.1 Summary

### **HTML, HEAD, and BODY Tags**

http.htmlOpen, http.htmlClose - generate <HTML> and </HTML>

http.headOpen, http.headClose - generate <HEAD> and </HEAD>

http.bodyOpen, http.bodyClose - generate <BODY> and </BODY>

### **Comment Tag**

http.comment - generates <!-- and -->

### **Tags in the <HEAD> Area**

http.base - generates <BASE>

http.linkRel - generates <LINK> with the REL attribute

http.linkRev - generates <LINK> with the REV attribute

http.title - generates <TITLE>

http.meta - generates <META>

http.script - generates <SCRIPT>

http.style - generates <STYLE>

http.isindex - generates <ISINDEX>

### **Applet Tags**

http.appletopen, http.appletclose - generate <APPLET> and </APPLET>

http.param - generates <PARAM>

### **List Tags**

http.olistOpen, http.olistClose - generate <OL> and </OL>

http.ulistOpen, http.ulistClose - generate <UL> and </UL>

http.dlistOpen, http.dlistClose - generate <DL> and </DL>

http.dlistTerm - generates <DT>

http.dlistDef - generates <DD>

http.dirlistOpen, http.dirlistClose - generate <DIR> and </DIR>



http.listHeader - generates <LH>

http.listingOpen, http.listingClose - generate <LISTING> and </LISTING>

http.menulistOpen, http.menulistClose - generate <MENU> and </MENU>

http.listItem - generates <LI>

### **Form Tags**

http.formOpen, http.formClose - generate <FORM> and </FORM>

http.formCheckbox - generates <INPUT TYPE="CHECKBOX">

http.formHidden - generates <INPUT TYPE="HIDDEN">

http.formImage - generates <INPUT TYPE="IMAGE">

http.formPassword - generates <INPUT TYPE="PASSWORD">

http.formRadio - generates <INPUT TYPE="RADIO">

http.formSelectOpen, http.formSelectClose - generate <SELECT> and </SELECT>

http.formSelectOption - generates <OPTION>

http.formText - generates <INPUT TYPE="TEXT">

http.formTextarea, http.formTextarea2 - generate <TEXTAREA>

http.formTextareaOpen, http.formTextareaOpen2, http.formTextareaClose - generate <TEXTAREA> and </TEXTAREA>

http.formReset - generates <INPUT TYPE="RESET">

http.formSubmit - generates <INPUT TYPE="SUBMIT">

### **Table Tags**

http.tableOpen, http.tableClose - generate <TABLE> and </TABLE>

http.tableCaption - generates <CAPTION>

http.tableRowOpen, http.tableRowClose - generate <TR> and </TR>

http.tableHeader - generates <TH>

http.tableData - generates <TD>

htf.format\_cell - generates <TD>

### **IMG, HR, and A Tags**

http.line, http.hr - generate <HR>

http.img, http.img2 - generate <IMG>

http.anchor, http.anchor2 - generates <A>

http.mapOpen, http.mapClose - generate <MAP> and </MAP>

### **Paragraph Formatting Tags**

http.header - generates heading tags (<H1> to <H6>)

http.para, http.paragraph - generate <P>

http.print, http.prn - generate any text that is passed in

http.prints, http.ps - generate any text that is passed in; special characters in HTML are escaped

http.preOpen, http.preClose - generate <PRE> and </PRE>

http.blockquoteOpen, http.blockquoteClose - generate <BLOCKQUOTE> and </BLOCKQUOTE>

http.div - generates <DIV>

http.nl, http.br - generate <BR>

http.nobr - generates <NOBR>

http.wbr - generates <WBR>

http.plaintext - generates <PLAINTEXT>

http.address - generates <ADDRESS>

http.mailto - generates <A> with the MAILTO attribute

http.area - generates <AREA>

http.bgsound - generates <BGSOUND>

### **Character Formatting Tags**

http.basefont - generates <BASEFONT>

http.big - generates <BIG>

http.bold - generates <B>

http.center - generates <CENTER> and </CENTER>

http.centerOpen, http.centerClose - generate <CENTER> and </CENTER>

http.cite - generates <CITE>

http.code - generates <CODE>

http.dfn - generates <DFN>

http.get\_download\_files\_list - generate <EM>

http.fontOpen, http.fontClose - generate <FONT> and </FONT>

http.italic - generates <I>

http.keyboard, http.kbd - generate <KBD> and </KBD>

http.s - generates <S>

http.sample - generates <SAMP>

http.small - generates <SMALL>

http.strike - generates <STRIKE>

http.strong - generates <STRONG>

http.sub - generates <SUB>

http.sup - generates <SUP>

http.teletype - generates <TT>

http.underline - generates <U>

http.variable - generates <VAR>

### **Frame Tags**

http.frame - generates <FRAME>

http.framesetOpen, http.framesetClose - generate <FRAMESET> and </FRAMESET>

http.noframesOpen, http.noframesClose - generate <NOFRAMES> and </NOFRAMES>

## 1.2 htp.address

This generates the <ADDRESS> and </ADDRESS> tags, which specify the address, author and signature of a document.

**Table 1–1** *htp.address*

Properties	Definitions
Syntax:	<pre> htp.address (     cvalue          in          varchar2     cnowrap         in          varchar2  DEFAULT NULL     cclear          in          varchar2  DEFAULT NULL     cattributes     in          varchar2  DEFAULT NULL); htf.address (cvalue, cnowrap, cclear, cattributes) return varchar2; </pre>
Parameters:	<p><b>cvalue</b> - the string that goes between the &lt;ADDRESS&gt; and &lt;/ADDRESS&gt; tags.</p> <p><b>cnowrap</b> - if the value for this parameter is not NULL, the NOWRAP attribute is included in the tag.</p> <p><b>cclear</b> - the value for the CLEAR attribute.</p> <p><b>cattributes</b> - other attributes to be included as-is in the tag.</p>
Generates:	<pre>&lt;ADDRESS CLEAR="cclear" NOWRAP cattributes&gt;cvalue&lt;/ADDRESS&gt;</pre>

## 1.3 htp.anchor, htp.anchor2

These generate the <A> and </A> HTML tags, which specify the source or destination of a hypertext link. This tag accepts several attributes, but either HREF or NAME is required. HREF specifies to where to link. NAME allows this tag to be a target of a hypertext link. The difference between these subprograms is that htp.anchor2 provides a target and therefore can be used for a frame.

**Table 1–2** *htp.anchor,htp.anchor2*

Properties	Definitions
Syntax:	<pre> htp.anchor (     curl          in          varchar2     ctext         in          varchar2     cname         in          varchar2   DEFAULT NULL     cattributes   in          varchar2   DEFAULT NULL); htf.anchor (curl, ctext, cname, cattributes) return varchar2;  htp.anchor2 (     curl          in          varchar2     ctext         in          varchar2     cname         in          varchar2   DEFAULT NULL     ctarget       in          varchar2   DEFAULT NULL     cattributes   in          varchar2   DEFAULT NULL); htf.anchor2 (curl, ctext, cname, ctarget, cattributes) return varchar2; </pre>
Parameters:	<p>curl - the value for the HREF attribute.</p> <p>ctext - the string that goes between the &lt;A&gt; and &lt;/A&gt; tags.</p> <p>cname - the value for the NAME attribute.</p> <p>ctarget - the value for the TARGET attribute.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<pre> &lt;A HREF="curl" NAME="cname" cattributes&gt;ctext&lt;/A&gt; &lt;A HREF="curl" NAME="cname" TARGET = "ctarget" cattributes&gt;ctext&lt;/A&gt; </pre>

## 1.4 htp.appletopen, htp.appletclose

htp.appletopen generates the <APPLET> HTML tag, which begins the invocation of a Java applet. Close the applet invocation with htp.appletclose, which generates the </APPLET> HTML tag.

Specify parameters to the Java applet using the htp.param procedure.

Use the cattributes parameter to specify the CODEBASE attribute since the PL/SQL cartridge does not know where to find the class files. The CODEBASE attribute specifies the virtual path containing the class files.

**Table 1–3** *htp.appletopen, htp.appletclose*

Properties	Definitions
Syntax:	<pre> htp.appletopen(     ccode          in          varchar2     cheight        in          number     cwidth         in          number     cattributes    in          varchar2  DEFAULT NULL); htf.appletopen(ccode, cheight, cwidth, cattributes) return varchar2;  htp.appletclose; htf.appletclose return varchar2; </pre>
Parameters:	<p><i>ccode</i> - the value for the CODE attribute, which specifies the name of the applet class.</p> <p><i>cheight</i> - the value for the HEIGHT attribute.</p> <p><i>cwidth</i> - the value for the WIDTH attribute.</p> <p><i>cattributes</i> - other attributes to be included as-is in the tag.</p>
Generates:	<pre> &lt;APPLET CODE=<i>ccode</i> HEIGHT=<i>cheight</i> WIDTH=<i>cwidth</i> <i>cattributes</i>&gt; &lt;/APPLET&gt; </pre>
Example:	<pre> htp.appletopen('testclass.class', 100, 200, 'CODEBASE="/ows-applets"')  generates  &lt;APPLET CODE="testclass.class" height=100 width=200 CODEBASE="/ows-applets"&gt; </pre>

---

## 1.5 htp.area

This generates the <AREA> HTML tag, which defines a client-side image map. The <AREA> tag defines areas within the image and destinations for the areas.

**Table 1–4** *htp.area*

Properties	Definitions
Syntax:	<pre> htp.area(     ccoords      in      varchar2     cshape       in      varchar2  DEFAULT NULL     chref        in      varchar2  DEFAULT NULL     cnohref      in      varchar2  DEFAULT NULL     ctargt       in      varchar2  DEFAULT NULL     cattributes  in      varchar2  DEFAULT NULL); htf.area(ccoords, cshape, chref, cnohref, ctargt, cattributes) return varchar2; </pre>
Parameters:	<p>ccoords - the value for the COORDS attribute.</p> <p>cshape - the value for the SHAPE attribute.</p> <p>chref - the value for the HREF attribute.</p> <p>cnohref - if the value for this parameter is not NULL, the NOHREF attribute is added to the tag.</p> <p>ctargt - the value for the TARGET attribute.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<pre> &lt;AREA COORDS="<i>ccoords</i>" SHAPE="<i>cshape</i>" HREF="<i>chref</i>" NOHREF TARGET="<i>ctargt</i>" <i>cattributes</i>&gt; </pre>

## 1.6 htp.base

This generates the <BASE> HTML tag, which records the URL of the document.

**Table 1–5** *htp.base*

Properties	Definitions
Syntax:	<pre> htp.base(     ctargt       in      varchar2  DEFAULT NULL     cattributes  in      varchar2  DEFAULT NULL); htf.base(ctargt, cattributes) return varchar2; </pre>
Parameters:	<p>ctargt - the value for the TARGET attribute, which establishes a window name to which all links in this document are targeted.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<pre> &lt;BASE HREF="<i>&lt;current URL&gt;</i>" TARGET="<i>ctargt</i>" <i>cattributes</i>&gt; </pre>

## 1.7 htp.basefont

This generates the <BASEFONT> HTML tag, which specifies the base font size for a Web page.

**Table 1–6** *htp.basefont*

Properties	Definitions
Syntax:	<pre>htp.basefont(nsize in integer); htf.basefont(nsize) return varchar2;</pre>
Parameters:	nsize - the value for the SIZE attribute.
Generates:	<BASEFONT SIZE=" <i>nsize</i> ">

## 1.8 htp.bgsound

This generates the <BGSOUND> HTML tag, which includes audio for a Web page.

**Table 1–7** *htp.bgsound*

Properties	Definitions
Syntax:	<pre>htp.bgsound(   csrc          in          varchar2   cloop         in          varchar2  DEFAULT NULL   cattributes   in          varchar2  DEFAULT NULL); htf.bgsound(csrc, cloop, cattributes) return varchar2;</pre>
Parameters:	<p>csrc - the value for the SRC attribute.</p> <p>cloop - the value for the LOOP attribute.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<BGSOUND SRC=" <i>csrc</i> " LOOP=" <i>cloop</i> " <i>cattributes</i> >

## 1.9 htp.big

This generates the <BIG> and </BIG> tags, which direct the browser to render the text in a bigger font.



**Table 1–8** *htp.big*

Properties	Definitions
Syntax:	<pre>htp.big(     ctext          in          varchar2     cattributes    in          varchar2  DEFAULT NULL); htf.big(ctext, cattributes) return varchar2;</pre>
Parameters:	<p>ctext - the text that goes between the tags.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<BIG <i>cattributes</i> > <i>ctext</i> </BIG>

## 1.10 htp.blockquoteOpen, htp.blockquoteClose

This generates the <BLOCKQUOTE> and </BLOCKQUOTE> tag, which mark a section of quoted text.

**Table 1–9** *htp.blockquoteOpen, htp.blockquoteClose*

Properties	Definitions
Syntax:	<pre>htp.blockquoteOpen (     cnowrap        in          varchar2  DEFAULT NULL     cclear         in          varchar2  DEFAULT NULL     cattributes    in          varchar2  DEFAULT NULL); htf.blockquoteOpen (cnowrap, cclear, cattributes) return varchar2;  htp.blockquoteClose; htf.blockquoteClose return varchar2;</pre>
Parameters:	<p>cnowrap - if the value for this parameter is not NULL, the NOWRAP attribute is added to the tag.</p> <p>cclear - the value for the CLEAR attribute.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<BLOCKQUOTE CLEAR=" <i>cclear</i> " NOWRAP <i>cattributes</i> > </BLOCKQUOTE>

## 1.11 htp.bodyOpen, htp.bodyClose

This generates the <BODY> and </BODY> tags, which mark the body section of an HTML document.

**Table 1–10** *htp.bodyOpen, htp.bodyClose*

Properties	Definitions
Syntax:	<pre> htp.bodyOpen(     cbackground    in    varchar2    DEFAULT NULL     cattributes    in    varchar2    DEFAULT NULL); htf.bodyOpen(cbackground, cattributes) return varchar2;  htp.bodyClose; htf.bodyClose return varchar2; </pre>
Parameters:	<p><b>cbackground</b> - the value for the BACKGROUND attribute, which specifies a graphic file to use for the background of the document.</p> <p><b>cattributes</b> - other attributes to be included as-is in the tag.</p>
Generates:	<pre> &lt;BODY background="<b>cbackground</b>" <b>cattributes</b>&gt; &lt;/BODY&gt; </pre>
Example:	<pre> htp.bodyOpen('/img/background.gif'); generates: &lt;BODY background="/img/background.gif"&gt; </pre>

---

## 1.12 htp.bold

This generates the <B> and </B> tags, which direct the browser to display the text in boldface.

**Table 1–11** *htp.bold*

Properties	Definitions
Syntax:	<pre> htp.bold (     ctext          in    varchar2     cattributes    in    varchar2    DEFAULT NULL); htf.bold (ctext, cattributes) return varchar2; </pre>
Parameters:	<p><b>ctext</b> - the text that goes between the tags.</p> <p><b>cattributes</b> - other attributes to be included as-is in the tag.</p>
Generates:	<pre> &lt;B <b>cattributes</b>&gt;ctext&lt;/B&gt; </pre>

---

## 1.13 htp.center

This generates the <CENTER> and </CENTER> tags, which center a section of text within a Web page.

**Table 1–12** *htp.center*

Properties	Definitions
Syntax:	<code>htp.center(ctext in varchar2);</code> <code>htf.center(ctext in varchar2) return varchar2;</code>
Parameters:	ctext - the text to center.
Generates:	<code>&lt;CENTER&gt;ctext&lt;/CENTER&gt;</code>

## 1.14 htp.centerOpen, htp.centerClose

This generates the `<CENTER>` and `</CENTER>` tags, which mark the section of text to center.

**Table 1–13** *htp.centerOpen, htp.centerClose*

Properties	Definitions
Syntax:	<code>htp.centerOpen;</code> <code>htf.centerOpen return varchar2;</code>  <code>htp.centerClose;</code> <code>htf.centerClose return varchar2;</code>
Parameters:	None
Generates:	<code>&lt;CENTER&gt;</code> <code>&lt;/CENTER&gt;</code>

## 1.15 htp.cite

This generates the `<CITE>` and `</CITE>` tags, which direct the browser to render the text as citation.

**Table 1–14** *htp.cite*

Properties	Definitions
Syntax:	<pre>htp.cite (     ctext          in          varchar2     cattributes    in          varchar2  DEFAULT NULL); htf.cite (ctext, cattributes) return varchar2;</pre>
Parameters:	<p>ctext - the text to render as citation.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<code>&lt;CITE cattributes&gt;ctext&lt;/CITE&gt;</code>

## 1.16 htp.code

This generates the `<CODE>` and `</CODE>` tags, which direct the browser to render the text in monospace font.

**Table 1–15** *htp.code*

Properties	Definitions
Syntax:	<pre>htp.code (     ctext          in          varchar2     cattributes    in          varchar2  DEFAULT NULL); htf.code (ctext, cattributes) return varchar2;</pre>
Parameters:	<p>ctext - the text to render as code.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<code>&lt;CODE cattributes&gt;ctext&lt;/CODE&gt;</code>

## 1.17 htp.comment

This generates the comment tags.

**Table 1–16** *htp.comment*

Properties	Definitions
Syntax:	<pre>htp.comment (ctext in varchar2); htf.comment (ctext in varchar2) return varchar2;</pre>
Parameters:	ctext - the comment.
Generates:	<code>&lt;!-- ctext --&gt;</code>

## 1.18 htp.dfn

This generates the `<DFN>` and `</DFN>` tags, which direct the browser to render the text in italics.

**Table 1–17** *htp.dfn*

Properties	Definitions
Syntax:	<code>htp.dfn(ctext in varchar2);</code> <code>htf.dfn(ctext in varchar2) return varchar2;</code>
Parameters:	<code>ctext</code> - the text to render in italics.
Generates:	<code>&lt;DFN&gt;ctext&lt;/DFN&gt;</code>

## 1.19 htp.dirlistOpen, htp.dirlistClose

This generates the `<DIR>` and `</DIR>` tags, which create a directory list section. A directory list presents a list of items that contains up to 20 characters. Items in this list are typically arranged in columns, 24 characters wide. The `<LI>` tag or `htp.listItem` must appear directly after this tag to define the items in the list.

**Table 1–18** *htp.dirlistOpen, htp.dirlistClose*

Properties	Definitions
Syntax:	<code>htp.dirlistOpen;</code> <code>htf.dirlistOpen return varchar2;</code>  <code>htp.dirlistClose;</code> <code>htf.dirlistClose return varchar2;</code>
Parameters:	None
Generates:	<code>&lt;DIR&gt;</code> <code>&lt;/DIR&gt;</code>

## 1.20 htp.div

This generates the `<DIV>` tag, which creates document divisions.

**Table 1–19** *http.div*

Properties	Definitions
Syntax:	<pre> http.div(     calign          in          varchar2  DEFAULT NULL     cattributes    in          varchar2  DEFAULT NULL); htf.div(calign, cattributes) return varchar2; </pre>
Parameters:	<p>calign - the value for the ALIGN attribute.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<DIV ALIGN=" <i>calign</i> " <i>cattributes</i> >

## 1.21 http.dlistOpen, http.dlistClose

This generates the <DL> and </DL> tags, which create a definition list. A definition list looks like a glossary: it contains terms and definitions. Terms are inserted using http.dlistTerm, and definitions are inserted using http.dlistDef.

**Table 1–20** *http.dlistOpen, http.dlistClose*

Properties	Definitions
Syntax:	<pre> http.dlistOpen (     cclear          in          varchar2  DEFAULT NULL     cattributes    in          varchar2  DEFAULT NULL); htf.dlistOpen (cclear, cattributes) return varchar2;  http.dlistClose; htf.dlistClose return varchar2; </pre>
Parameters:	<p>cclear - the value for the CLEAR attribute.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<DL CLEAR=" <i>cclear</i> " <i>cattributes</i> > </DL>

## 1.22 http.dlistDef

This generates the <DD> tag, which inserts definitions of terms. Use this tag for a definition list <DL>. Terms are tagged <DT> and definitions are tagged <DD>.

**Table 1–21** *htp.dlistDef*

Properties	Definitions
Syntax:	<pre> htp.dlistDef(     ctext          in          varchar2  DEFAULT NULL     cclear         in          varchar2  DEFAULT NULL     cattributes    in          varchar2  DEFAULT NULL); htf.dlistDef(ctext, cclear, cattributes) return varchar2; </pre>
Parameters:	<p>ctext - the definition for the term.</p> <p>cclear - the value for the CLEAR attribute.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<DD CLEAR="cclear" cattributes>ctext

## 1.23 htp.dlistTerm

This generates the <DT> tag, which defines a term in a definition list <DL>.

**Table 1–22** *htp.dlistTerm*

Properties	Definitions
Syntax:	<pre> htp.dlistTerm (     ctext          in          varchar2  DEFAULT NULL     cclear         in          varchar2  DEFAULT NULL     cattributes    in          varchar2  DEFAULT NULL); htf.dlistTerm (ctext, cclear, cattributes) return varchar2; </pre>
Parameters:	<p>ctext - the term.</p> <p>cclear - the value for the CLEAR attribute.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<DT CLEAR="cclear" cattributes>ctext

## 1.24 htp.download\_file

After uploading files to the database, you can download them, delete them from the database, and read and write their attributes.

**Table 1–23** *http.download\_file*

Properties	Definitions
Syntax:	<pre>http.download_file(sFileName in varchar2) http.download_file(bCompress in boolean DEFAULT FALSE);</pre>
Parameters:	<p>sFileName - file to be downloaded.</p> <p>bCompress - file to be compressed.</p>
Generates:	The downloaded file.

## 1.25 http.get\_download\_files\_list

After you have downloaded files to the database, you need to get the files.

**Table 1–24** *http.get\_download\_files\_list*

Properties	Definitions
Syntax:	<pre>http.get_download_files_list(sFileName out varchar2) http.get_download_files_list(bCompress out binary_integer);</pre>
Parameters:	<p>sFileName - file to get.</p> <p>bCompress - file to compress.</p>
Generates:	The downloaded file.

## 1.26 http.emphasis, http.em

This generates the <EM> and </EM> tags, which define text to be emphasized.



**Table 1–25** *htp.emphasis, htp.em*

Properties	Definitions
Syntax:	<pre> htp.em (     ctext          in          varchar2     cattributes    in          varchar2  DEFAULT NULL); htf.em (ctext, cattributes) return varchar2;  htp.emphasis (     ctext          in          varchar2     cattributes    in          varchar2  DEFAULT NULL); htf.emphasis (ctext, cattributes) return varchar2; </pre>
Parameters:	<p>ctext - the text to emphasize.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<EM <i>cattributes</i> >ctext</EM>

## 1.27 htf.escape\_sc

This replaces characters that have special meaning in HTML with their escape sequences. The following characters are converted:

- & to &amp;
- " to &quot;
- < to &lt;
- > to &gt;

The procedure version of this subprogram does the same thing as htp.prints and htp.ps.

**Table 1–26** *htf.escape\_sc*

Properties	Definitions
Syntax:	<pre> htf.escape_sc(ctext in varchar2) return varchar2; htf.escape_sc(ctext in varchar2); </pre>
Parameters:	ctext - the string to convert.
Generates:	The converted string.

## 1.28 htf.escape\_url

This replaces characters that have special meaning in HTML and HTTP with their escape sequences. The following characters are converted:

& to &amp;  
 " to &quot;  
 < to &lt;  
 > to &gt;  
 % to &25

**Table 1–27** *htf.escape\_ur*

Properties	Definitions
Syntax:	<code>htf.escape_url(p_url in varchar2) return varchar2;</code>
Parameters:	<code>p_url</code> - the string to convert.
Generates:	The converted string.

## 1.29 htp.fontOpen, htp.fontClose

This generates the <FONT> and </FONT> tags, which mark a section of text with the specified font characteristics.

**Table 1–28** *htp.fontOpen,htp.fontClose*

Properties	Definitions
Syntax:	<pre> htp.fontOpen(     ccolor          in          varchar2  DEFAULT NULL     cface           in          varchar2  DEFAULT NULL     csize           in          varchar2  DEFAULT NULL     cattributes     in          varchar2  DEFAULT NULL); htf.fontOpen(ccolor, cface, csize, cattributes) return varchar2;  htp.fontClose; htf.fontClose return varchar2; </pre>
Parameters:	<p><code>ccolor</code> - the value for the COLOR attribute.</p> <p><code>cface</code> - the value for the FACE attribute.</p> <p><code>csize</code> - the value for the SIZE attribute.</p> <p><code>cattributes</code> - other attributes to be included as-is in the tag.</p>
Generates:	<pre> &lt;FONT COLOR="ccolor" FACE="cface" SIZE="csize" cattributes&gt; &lt;/FONT&gt; </pre>

## 1.30 htf.format\_cell

This formats column values inside an HTML table using `htf.tableData`. It allows better control over the HTML tables.

**Table 1–29** *htf.format\_cell*

Properties	Definitions
Syntax:	<pre>htf.format_cell (     columnValue      in      varchar2     format_numbers   in      varchar2  DEFAULT NULL) return     varchar2;</pre>
Parameters:	<p><code>columnValue</code> - the value that needs to be formatted in an HTML table.</p> <p><code>format_numbers</code> - the format that numeric data is displayed in. If the value of this parameter is not Null, number fields are right-justified and rounded to two decimal places.</p>
Generates:	<code>&lt;TD &gt;columnValue&lt;/TD&gt;</code>

## 1.31 htp.formCheckbox

This generates the `<INPUT>` tag with `TYPE="checkbox"`, which inserts a checkbox element in a form. A checkbox element is a button that the user toggles on or off.

**Table 1–30** *htp.formCheckbox*

Properties	Definitions
Syntax:	<pre>htp.formCheckbox (     cname      in      varchar2     cvalue     in      varchar2  DEFAULT 'on'     cchecked   in      varchar2  DEFAULT NULL     cattributes in      varchar2  DEFAULT NULL); htp.formCheckbox (cname, cvalue, cchecked, cattributes) return     varchar2;</pre>
Parameters:	<p><code>cname</code> - the value for the NAME attribute.</p> <p><code>cvalue</code> - the value for the VALUE attribute.</p> <p><code>cchecked</code> - if the value for this parameter is not NULL, the CHECKED attribute is added to the tag.</p> <p><code>cattributes</code> - other attributes to be included as-is in the tag.</p>
Generates:	<code>&lt;INPUT TYPE="checkbox" NAME="cname" VALUE="cvalue" CHECKED cattributes&gt;</code>

## 1.32 http.formOpen, http.formClose

This generates the <FORM> and </FORM> tags, which create a form section in an HTML document.

**Table 1–31** *http.formOpen, http.formClose*

Properties	Definitions
Syntax:	<pre> http.formOpen (     curl          in          varchar2     cmethod       in          varchar2   DEFAULT 'POST'     ctargt        in          varchar2   DEFAULT NULL     cencntype     in          varchar2   DEFAULT NULL     catttributes  in          varchar2   DEFAULT NULL); htf.formOpen (curl, cmethod, ctargt, cencntype, catttributes) return varchar2;  http.formClose; htf.formClose return varchar2; </pre>
Parameters:	<p>curl - the URL of the WRB or CGI script where the contents of the form is sent. This parameter is required.</p> <p>cmethod - the value for the METHOD attribute. The value can be "GET" or "POST".</p> <p>ctargt - the value for the TARGET attribute.</p> <p>cencntype - the value for the ENCTYPE attribute.</p> <p>catttributes - other attributes to be included as-is in the tag.</p>
Generates:	<pre> &lt;FORM ACTION="<i>curl</i>" METHOD="<i>cmethod</i>" TARGET="<i>ctargt</i>" ENCTYPE="<i>cencntype</i>" <i>catttributes</i>&gt; &lt;/FORM&gt; </pre>

---

## 1.33 http.formFile

This generates the <INPUT> tag with TYPE="hidden", which inserts a hidden form element. This element is not seen by the user. It submits additional values to the script.

**Table 1–32** *htp.formFile*

Properties	Definitions
Syntax:	<pre>function formFile(     cname          in          varchar2     caccept        in          varchar2  DEFAULT NULL     cattributes    in          varchar2  DEFAULT NULL); htf.formFile (cname, caccept, cattributes) return varchar2;</pre>
Parameters:	<p>cname - the value for the NAME attribute.</p> <p>caccept - a coma seperated list of MIME types for upload</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<INPUT TYPE="file" NAME=" <i>cname</i> " ACCEPT=" <i>caccept</i> " <i>cattributes</i> >

## 1.34 htp.formHidden

This generates the <INPUT> tag with TYPE="hidden", which inserts a hidden form element. This element is not seen by the user. It submits additional values to the script.

**Table 1–33** *htp.formHidden*

Properties	Definitions
Syntax:	<pre>htp.formHidden (     cname          in          varchar2     cvalue         in          varchar2  DEFAULT NULL     cattributes    in          varchar2  DEFAULT NULL); htf.formHidden (cname, cvalue, cattributes) return varchar2;</pre>
Parameters:	<p>cname - the value for the NAME attribute.</p> <p>cvalue - the value for the VALUE attribute.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<INPUT TYPE="hidden" NAME=" <i>cname</i> " VALUE=" <i>cvalue</i> " <i>cattributes</i> >

## 1.35 htp.formImage

This generates the <INPUT> tag with TYPE="image", which creates an image field that the user clicks to submit the form immediately. The coordinates of the selected point are measured in pixels, and returned (along with other contents of the form) in two name/value pairs. The x coordinate is submitted under the name of the field

with .x appended, and the y coordinate with .y appended. Any VALUE attribute is ignored.

**Table 1–34** *htp.formImage*

Properties	Definitions
Syntax:	<pre> htp.formImage (     cname          in          varchar2     csrc           in          varchar2     calign         in          varchar2  DEFAULT NULL     cattributes   in          varchar2  DEFAULT NULL); htf.formImage (cname, csrc, calign, cattributes) return varchar2; </pre>
Parameters:	<p>cname - the VALUE for the NAME attribute.</p> <p>csrc - the value for the SRC attribute, which specifies the image file.</p> <p>calign - the value for the ALIGN attribute.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<pre>&lt;INPUT TYPE="image" NAME="cname" SRC="csrc" ALIGN="calign" cattributes&gt;</pre>

## 1.36 htp.formPassword

This generates the <INPUT> tag with TYPE="password", which creates a single-line text entry field. When the user enters text in the field, each character is represented by one asterisk. This is used for entering passwords.

**Table 1–35** *htp.formPassword*

Properties	Definitions
Syntax:	<pre> htp.formPassword (     cname      in      varchar2     csize      in      varchar2     cmaxlength in      varchar2  DEFAULT NULL     cvalue     in      varchar2  DEFAULT NULL     cattributes in      varchar2  DEFAULT NULL); htf.formPassword (cname, csize, cmaxlength, cvalue, cattributes) return varchar2; </pre>
Parameters:	<p>cname - the value for the NAME attribute.</p> <p>csize - the value for the SIZE attribute.</p> <p>cmmaxlength - the value for the MAXLENGTH attribute.</p> <p>cvalue - the value for the VALUE attribute.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<pre> &lt;INPUT TYPE="password" NAME="cname" SIZE="csize" MAXLENGTH="cmmaxlength" VALUE="cvalue" cattributes&gt; </pre>

## 1.37 htp.formRadio

This generates the <INPUT> tag with TYPE="radio", which creates a radio button on the HTML form. Within a set of radio buttons, the user selects only one. Each radio button in the same set has the same name, but different values. The selected radio button generates a name/value pair.

**Table 1–36** *htp.formRadio*

Properties	Definitions
Syntax:	<pre> htp.formRadio (     cname          in          varchar2     cvalue         in          varchar2     cchecked       in          varchar2  DEFAULT NULL     cattributes    in          varchar2  DEFAULT NULL); htf.formRadio (cname, cvalue, cchecked, cattributes) return varchar2; </pre>
Parameters:	<p>cname - the value for the NAME attribute.</p> <p>cvalue - the value for the VALUE attribute.</p> <p>cchecked - if the value for this parameter is not NULL, the CHECKED attribute is added to the tag.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<pre>&lt;INPUT TYPE="radio" NAME="cname" VALUE="cvalue" CHECKED cattributes&gt;</pre>

## 1.38 htp.formReset

This generates the <INPUT> tag with TYPE="reset", which creates a button that, when selected, resets the form fields to their initial values.

**Table 1–37** *htp.formReset*

Properties	Definitions
Syntax:	<pre> htp.formReset (     cvalue         in          varchar2  DEFAULT 'Reset'     cattributes    in          varchar2  DEFAULT NULL); htf.formReset (cvalue, cattributes) return varchar2; </pre>
Parameters:	<p>cvalue - the value for the VALUE attribute.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<pre>&lt;INPUT TYPE="reset" VALUE="cvalue" cattributes&gt;</pre>

## 1.39 htp.formSelectOpen, htp.formSelectClose

This generates the <SELECT> and </SELECT> tags, which creates a Select form element. A Select form element is a listbox where the user selects one or more values. The values are inserted using htp.formSelectOption.



**Table 1–38** *htp.formSelectOpen,htp.formSelectClose*

Properties	Definitions
Syntax:	<pre> htp.formSelectOpen (   cname          in          varchar2   cprompt        in          varchar2  DEFAULT NULL   nsize          in          integer   DEFAULT NULL   cattributes    in          varchar2  DEFAULT NULL); htf.formSelectOpen (cname, cprompt, nsize, cattributes) return varchar2;  htp.formSelectClose; htf.formSelectClose return varchar2; </pre>
Parameters:	<p><b>cname</b> - the value for the NAME attribute.</p> <p><b>cprompt</b> - the string preceding the list box.</p> <p><b>nsize</b> - the value for the SIZE attribute.</p> <p><b>cattributes</b> - other attributes to be included as-is in the tag.</p>
Generates:	<pre> cprompt &lt;SELECT NAME="cname" SIZE="nsize" cattributes&gt; &lt;/SELECT&gt; </pre>
Example:	<pre> htp.formSelectOpen('greatest_player';   'Pick the greatest player:'); htp.formSelectOption('Messier'); htp.formSelectOption('Howe'); htp.formSelectOption('Gretzky'); htp.formSelectClose;  Generates: Pick the greatest player: &lt;SELECT NAME="greatest_player"&gt; &lt;OPTION&gt;Messier &lt;OPTION&gt;Howe &lt;OPTION&gt;Gretzky &lt;/SELECT&gt; </pre>

## 1.40 htp.formSelectOption

This generates the <OPTION> tag, which represents one choice in a Select element.

**Table 1–39** *htp.formSelectOption*

Properties	Definitions
Syntax:	<pre> htp.formSelectOption (     cvalue          in          varchar2     cselected       in          varchar2  DEFAULT NULL     cattributes     in          varchar2  DEFAULT NULL); htf.formSelectOption (cvalue, cselected, cattributes) return varchar2; </pre>
Parameters:	<p>cvalue - the text for the option.</p> <p>cselected - if the value for this parameter is not NULL, the SELECTED attribute is added to the tag.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<OPTION SELECTED <i>cattributes</i> > <i>cvalue</i>
Example:	See htp.formSelectOpen, htp.formSelectClose

## 1.41 htp.formSubmit

This generates the <INPUT> tag with TYPE="submit", which creates a button that, when clicked, submits the form.

If the button has a NAME attribute, the button contributes a name/value pair to the submitted data.

**Table 1–40** *htp.formSubmit*

Properties	Definitions
Syntax:	<pre> htp.formSubmit (     cname          in          varchar2  DEFAULT NULL     cvalue         in          varchar2  DEFAULT 'Submit'     cattributes    in          varchar2  DEFAULT NULL); htf.formSubmit (cname, cvalue, cattributes) return varchar2; </pre>
Parameters:	<p>cname - the value for the NAME attribute.</p> <p>cvalue - the value for the VALUE attribute.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<INPUT TYPE="submit" NAME=" <i>cname</i> " VALUE=" <i>cvalue</i> " <i>cattributes</i> >

## 1.42 htp.formText

This generates the <INPUT> tag with TYPE="text", which creates a field for a single line of text.

**Table 1–41** *htp.formText*

Properties	Definitions
Syntax:	<pre> htp.formText (     cname          in          varchar2     csize          in          varchar2  DEFAULT NULL     cmaxlength     in          varchar2  DEFAULT NULL     cvalue         in          varchar2  DEFAULT NULL     cattributes    in          varchar2  DEFAULT NULL); htf.formText (cname, csize, cmaxlength, cvalue, cattributes) return varchar2; </pre>
Parameters:	<p>cname - the value for the NAME attribute.</p> <p>csize - the value for the SIZE attribute.</p> <p>cmmaxlength - the value for the MAXLENGTH attribute.</p> <p>cvalue - the value for the VALUE attribute.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<pre> &lt;INPUT TYPE="text" NAME="<i>cname</i>" SIZE="<i>csize</i>" MAXLENGTH="<i>cmmaxlength</i>" VALUE="<i>cvalue</i>" <i>cattributes</i>&gt; </pre>

## 1.43 htp.formTextarea, htp.formTextarea2

This generates the <TEXTAREA> tag, which creates a text field that has no predefined text in the text area. This field enables entering several lines of text.

The difference between these subprograms is that htp.formTextarea2 has the cwrap parameter, which specifies a wrap style.

**Table 1–42** *http.formTextarea, http.formTextarea2*

Properties	Definitions
Syntax:	<pre> http.formTextarea (   cname          in          varchar2   nrows          in          integer   ncolumns       in          integer   calign         in          varchar2   DEFAULT NULL   cattributes    in          varchar2   DEFAULT NULL); htf.formTextarea (cname, nrows, ncolumns, calign, cattributes) return varchar2;  http.formTextarea2 (   cname          in          varchar2   nrows          in          integer   ncolumns       in          integer   calign         in          varchar2   DEFAULT NULL   cwrap         in          varchar2   DEFAULT NULL   cattributes    in          varchar2   DEFAULT NULL); htf.formTextarea2 (cname, nrows, ncolumns, calign, cwrap, cattributes) return varchar2; </pre>
Parameters:	<p><b>cname</b> - the value for the NAME attribute.</p> <p><b>nrows</b> - the value for the ROWS attribute. This is an integer.</p> <p><b>ncolumns</b> - the value for the COLS attribute. This is an integer.</p> <p><b>calign</b> - the value for the ALIGN attribute.</p> <p><b>cwrap</b> - the value for the WRAP attribute.</p> <p><b>cattributes</b> - other attributes to be included as-is in the tag.</p>
Generates:	<pre> &lt;TEXTAREA NAME="<i>cname</i>" ROWS="<i>nrows</i>" COLS="<i>ncolumns</i>" ALIGN="<i>calign</i>" <i>cattributes</i>&gt;&lt;/TEXTAREA&gt;  &lt;TEXTAREA NAME="<i>cname</i>" ROWS="<i>nrows</i>" COLS="<i>ncolumns</i>" ALIGN="<i>calign</i>" WRAP="<i>cwrap</i>" <i>cattributes</i>&gt;&lt;/TEXTAREA&gt; </pre>

---

## 1.44 http.formTextareaOpen, http.formTextareaOpen2, http.formTextareaClose

This generates the <TEXTAREA> and </TEXTAREA> tags, which creates a text area form element. The difference between the two open subprograms is that http.formTextareaOpen2 has the cwrap parameter, which specifies a wrap style.

**Table 1–43** *http.formTextareaOpen, http.formTextareaOpen2, http.formTextareaClose*

Properties	Definitions
Syntax:	<pre> http.formTextareaOpen (     cname          in          varchar2     nrows          in          integer     ncolumns       in          integer     calign         in          varchar2   DEFAULT NULL     cattributes    in          varchar2   DEFAULT NULL); htf.formTextareaOpen (cname, nrows, ncolumns, calign, cattributes) return varchar2;  http.formTextareaOpen2(     cname          in          varchar2     nrows          in          integer     ncolumns       in          integer     calign         in          varchar2   DEFAULT NULL     cwrap          in          varchar2   DEFAULT NULL     cattributes    in          varchar2   DEFAULT NULL); htf.formTextareaOpen2(cname, nrows, ncolumns, calign, cwrap, cattributes) return varchar2;  http.formTextareaClose; htf.formTextareaClose return varchar2; </pre>
Parameters:	<p><b>cname</b> - the value for the NAME attribute.</p> <p><b>nrows</b> - the value for the ROWS attribute. This is an integer.</p> <p><b>ncolumns</b> - the value for the COLS attribute. This is an integer.</p> <p><b>calign</b> - the value for the ALIGN attribute.</p> <p><b>cwrap</b> - the value for the WRAP attribute.</p> <p><b>cattributes</b> - other attributes to be included as-is in the tag.</p>
Generates:	<pre> &lt;TEXTAREA NAME="<i>cname</i>" ROWS="<i>nrows</i>" COLS="<i>ncolumns</i>" ALIGN="<i>calign</i>" <i>cattributes</i>&gt; &lt;TEXTAREA NAME="<i>cname</i>" ROWS="<i>nrows</i>" COLS="<i>ncolumns</i>" ALIGN="<i>calign</i>" WRAP = "<i>cwrap</i>" <i>cattributes</i>&gt; &lt;/TEXTAREA&gt; </pre>

## 1.45 http.frame

This generates the <FRAME> tag, which defines the characteristics of a frame created by a <FRAMESET> tag.

**Table 1–44** *htp.frame*

Properties	Definitions
Syntax:	<pre> htp.frame(     csrc          in      varchar2     cname         in      varchar2  DEFAULT NULL     cmarginwidth  in      varchar2  DEFAULT NULL     cmarginheight in      varchar2  DEFAULT NULL     cscrolling    in      varchar2  DEFAULT NULL     cnoresize     in      varchar2  DEFAULT NULL     cattributes   in      varchar2  DEFAULT NULL); htf.frame(csrc, cname, cmarginwidth, cmarginheight, cscrolling, cnoresize, cattributes) return varchar2; </pre>
Parameters:	<p><i>csrc</i> - the URL to display in the frame.</p> <p><i>cname</i> - the value for the NAME attribute.</p> <p><i>cmarginwidth</i> - the value for the MARGINWIDTH attribute.</p> <p><i>cmarginheight</i> - the value for the MARGINHEIGHT attribute.</p> <p><i>cscrolling</i> - the value for the SCROLLING attribute.</p> <p><i>noresize</i> - if the value for this parameter is not NULL, the NORESIZE attribute is added to the tag.</p> <p><i>cattributes</i> - other attributes to be included as-is in the tag.</p>
Generates:	<pre> &lt;FRAME SRC="<i>csrc</i>" NAME="<i>cname</i>" MARGINWIDTH="<i>cmarginwidth</i>" MARGINHEIGHT="<i>cmarginheight</i>" SCROLLING="<i>cscrolling</i>" NORESIZE <i>cattributes</i>&gt; </pre>

---

## 1.46 htp.framesetOpen, htp.framesetClose

This generates the <FRAMESET> and </FRAMESET> tags, which define a frameset section.

**Table 1–45** *htp.framesetOpen, htp.framesetClose*

Properties	Definitions
Syntax:	<pre> htp.framesetOpen(   crows      in      varchar2  DEFAULT NULL   ccols      in      varchar2  DEFAULT NULL   cattributes in      varchar2  DEFAULT NULL); htf.framesetOpen(crows, ccols, cattributes) return varchar2;  htp.framesetClose; htf.framesetClose return varchar2; </pre>
Parameters:	<p>crows - the value for the ROWS attribute.</p> <p>ccols - the value for the COLS attribute.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<pre> &lt;FRAMESET ROWS="crows" COLS="ccols" cattributes&gt; &lt;/FRAMESET&gt; </pre>

## 1.47 htp.headOpen, htp.headClose

This generates the <HEAD> and </HEAD> tags, which mark the HTML document head section

**Table 1–46** *htp.headOpen, htp.headClose*

Properties	Definitions
Syntax:	<pre> htp.headOpen; htf.headOpen return varchar2;  htp.headClose; htf.headClose return varchar2; </pre>
Parameters:	<pre> &lt;&lt; &gt;&gt; </pre>
Generates:	<pre> &lt;HEAD&gt; &lt;/HEAD&gt; </pre>

## 1.48 htp.header

This generates opening heading tags (<H1> to <H6>) and their corresponding closing tags (</H1> to </H6>).

**Table 1–47** *htp.header*

Properties	Definitions
Syntax:	<pre>htp.header (   nsize      in   integer   cheader    in   varchar2   calign     in   varchar2 DEFAULT NULL   cnowrap    in   varchar2 DEFAULT NULL   cclear     in   varchar2 DEFAULT NULL   cattributes in   varchar2 DEFAULT NULL); htf.header (nsize, cheader, calign, cnowrap, cclear, cattributes) return varchar2;</pre>
Parameters:	<p>nsize - the heading level. This is an integer between 1 and 6.</p> <p>calign - the value for the ALIGN attribute.</p> <p>cheader - the text to display in the heading.</p> <p>cnowrap - the value for the NOWRAP attribute.</p> <p>cclear - the value for the CLEAR attribute.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<Hnsize ALIGN="calign" NOWRAP CLEAR="cclear" cattributes>cheader</Hnsize>
Example:	<pre>htp.header (1,'Overview'); produces: &lt;H1&gt;Overview&lt;/H1&gt;</pre>

---

## 1.49 htp.htmlOpen, htp.htmlClose

This generates the <HTML> and </HTML> tags, which mark the beginning and the end of an HTML document.

**Table 1–48** *htp.htmlOpen, htp.htmlClose*

Properties	Definitions
Syntax:	<pre>htp.htmlOpen; htf.htmlOpen return varchar2;  htp.htmlClose; htf.htmlClose return varchar2;</pre>
Parameters:	None.
Generates:	<HTML>
	</HTML>

---



## 1.50 htp.img, htp.img2

This generates the <IMG> tag, which directs the browser to load an image onto the HTML page. The difference between these subprograms is that htp.img2 uses the *cusemap* parameter.

**Table 1–49** *htp.img, htp.img2*

Properties	Definitions
Syntax:	<pre> htp.img (     curl          in      varchar2  DEFAULT NULL     calign        in      varchar2  DEFAULT NULL     calt          in      varchar2  DEFAULT NULL     cismap        in      varchar2  DEFAULT NULL     cattributes   in      varchar2  DEFAULT NULL); htf.img (curl, calign, calt, cismap, cattributes) return varchar2;  htp.img2(     curl          in      varchar2  DEFAULT NULL     calign        in      varchar2  DEFAULT NULL     calt          in      varchar2  DEFAULT NULL     cismap        in      varchar2  DEFAULT NULL     cusemap       in      varchar2  DEFAULT NULL     cattributes   in      varchar2  DEFAULT NULL); htf.img2(curl, calign, calt, cismap, cusemap, cattributes) return varchar2; </pre>
Parameters:	<p>curl - the value for the SRC attribute.</p> <p>calign - the value for the ALIGN attribute.</p> <p>calt - the value for the ALT attribute, which specifies alternative text to display if the browser does not support images.</p> <p>cismap - if the value for this parameter is not NULL, the ISMAP attribute is added to the tag. The attribute indicates that the image is an imagemap.</p> <p>cusemap - the value for the USEMAP attribute, which specifies a client-side image map.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<pre> &lt;IMG SRC="curl" ALIGN="calign" ALT="calt" ISMAP cattributes&gt;  &lt;IMG SRC="curl" ALIGN="calign" ALT="calt" ISMAP USEMAP="cusemap" cattributes&gt; </pre>

## 1.51 htp.isindex

This creates a single entry field with a prompting text, such as "*enter value*," then sends that value to the URL of the page or program.

**Table 1–50** *htp.isindex*

Properties	Definitions
Syntax:	<pre>htp.isindex (   cprompt      in      varchar2      DEFAULT NULL   curl         in      varchar2      DEFAULT NULL); htf.isindex (cprompt, curl) return varchar2;</pre>
Parameters:	<p>cprompt - the value for the PROMPT attribute.</p> <p>curl - the value for the HREF attribute.</p>
Generates:	<ISINDEX PROMPT=" <i>cprompt</i> " HREF=" <i>curl</i> " >

## 1.52 htp.italic

This generates the <I> and </I> tags, which direct the browser to render the text in italics

**Table 1–51** *htp.italic*

Properties	Definitions
Syntax	<pre>htp.italic (   ctext        in      varchar2   cattributes  in      varchar2      DEFAULT NULL); htf.italic (ctext, cattributes) return varchar2;</pre>
Parameters	<p>ctext - the text to be rendered in italics.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates	<I <i>cattributes</i> >ctext</I>

## 1.53 htp.keyboard, htp.kbd

This generates the <KBD> and </KBD> tags, which direct the browser to render the text in monospace. These subprograms do the same thing.

**Table 1–52** *htp.keyboard, htp.kbd*

Properties	Definitions
Syntax:	<pre> htp.keyboard (     ctext          in          varchar2     cattributes    in          varchar2  DEFAULT NULL); htf.keyboard (ctext, cattributes) return varchar2;  htp.kbd (     ctext          in          varchar2     cattributes    in          varchar2  DEFAULT NULL); htf.kbd (ctext, cattributes) return varchar2; </pre>
Parameters:	<p>ctext - the text to render in monospace.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<KBD <i>cattributes</i> > <i>ctext</i> </KBD>

## 1.54 htp.line, htp.hr

This generates the <HR> tag, which generates a line in the HTML document.

**Table 1–53** *htp.line, htp.hr*

Properties	Definitions
Purpose	Generates the <HR> tag, which generates a line in the HTML document.
Syntax	<pre> htp.line (     cclear          in          varchar2  DEFAULT NULL     csrc            in          varchar2  DEFAULT NULL     cattributes    in          varchar2  DEFAULT NULL); htf.line (cclear, csrc, cattributes) return varchar2;  htp.hr (     cclear          in          varchar2  DEFAULT NULL     csrc            in          varchar2  DEFAULT NULL     cattributes    in          varchar2  DEFAULT NULL); htf.hr (cclear, csrc, cattributes) return varchar2; </pre>
Parameters	<p>cclear - the value for the CLEAR attribute.</p> <p>csrc - the value for the SRC attribute, which specifies a custom image as the source of the line.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates	<HR CLEAR=" <i>cclear</i> " SRC=" <i>csrc</i> " <i>cattributes</i> >

## 1.55 htp.linkRel

This generates the <LINK> tag with the REL attribute, which gives the relationship described by the hypertext link from the anchor to the target. This is only used when the HREF attribute is present. This tag indicates a relationship between documents, but does not create a link. To create a link, use htp.anchor, htp.anchor2.

**Table 1–54** *htp.linkRel*

Properties	Directions
Syntax:	<pre> htp.linkRel (     crel          in          varchar2     curl          in          varchar2     ctitle       in          varchar2  DEFAULT NULL); htf.linkRel (crel, curl, ctitle) return varchar2;</pre>
Parameters:	<p>crel - the value for the REL attribute.</p> <p>curl - the value for the HREF attribute.</p> <p>ctitle - the value for the TITLE attribute.</p>
Generates:	<LINK REL=" <i>crel</i> " HREF=" <i>curl</i> " TITLE=" <i>ctitle</i> ">

## 1.56 htp.linkRev

This generates the <LINK> tag with the REV attribute, which gives the relationship described by the hypertext link from the target to the anchor. This is the opposite of htp.linkRel. This tag indicates a relationship between documents, but does not create a link. To create a link, use htp.anchor, htp.anchor2.

**Table 1–55** *htp.linkRev*

Properties	Definitions
Syntax:	<pre> htp.linkRev (     crev          in          varchar2     curl          in          varchar2     ctitle       in          varchar2  DEFAULT NULL); htf.linkRev (crev, curl, ctitle) return varchar2;</pre>
Parameters:	<p>crev - the value for the REV attribute.</p> <p>curl - the value for the HREF attribute</p> <p>ctitle - the value for the TITLE attribute.</p>
Generates	<LINK REV=" <i>crev</i> " HREF=" <i>curl</i> " TITLE=" <i>ctitle</i> ">

## 1.57 http.listHeader

This generates the <LH> and </LH> tags, which print an HTML tag at the beginning of the list.

**Table 1–56** *http.listHeader*

Properties	Definitions
Syntax:	<pre>http.listHeader (     ctext          in          varchar2     cattributes   in          varchar2  DEFAULT NULL); htf.listHeader (ctext, cattributes) return varchar2;</pre>
Parameters:	<p>ctext - the text to place between &lt;LH&gt; and &lt;/LH&gt;.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<LH <i>cattributes</i> > <i>ctext</i> </LH>

## 1.58 http.listingOpen, http.listingClose

This generates the <LISTING> and </LISTING> tags, which mark a section of fixed-width text in the body of an HTML page.

**Table 1–57** *http.listingOpen, http.listingClose*

Properties	Definitions
Syntax:	<pre>http.listingOpen; htf.listingOpen return varchar2;  http.listingClose; htf.listingClose return varchar2;</pre>
Parameters:	None.
Generates:	<LISTING>
	</LISTING>

## 1.59 http.listItem

This generates the <LI> tag, which indicates a list item.

**Table 1–58** *htp.listItem*

Properties	Definitions
Syntax:	<pre> htp.listItem (     ctext          in          varchar2  DEFAULT NULL     cclear         in          varchar2  DEFAULT NULL     cdingbat       in          varchar2  DEFAULT NULL     csrc           in          varchar2  DEFAULT NULL     cattributes    in          varchar2  DEFAULT NULL); htf.listItem (ctext, cclear, cdingbat, csrc, cattributes) return varchar2; </pre>
Parameters:	<p>ctext - the text for the list item.</p> <p>cclear - the value for the CLEAR attribute.</p> <p>cdingbat - the value for the DINGBAT attribute.</p> <p>csrc - the value for the SRC attribute.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<pre>&lt;LI CLEAR="cclear" DINGBAT="cdingbat" SRC="csrc" cattributes&gt;ctext</pre>

## 1.60 htp.mailto

This generates the <A> tag with the HREF set to 'mailto' prepended to the mail address argument.

**Table 1–59** *htp.mailto*

Properties	Definitions
Syntax:	<pre> htp.mailto (     caddress       in          varchar2     ctext          in          varchar2     cname          in          varchar2     cattributes    in          varchar2  DEFAULT NULL); htf.mailto (caddress, ctext, cname, cattributes) return varchar2; </pre>

**Table 1–59** *http.mailto*

Properties	Definitions
Parameters:	<p>address - the email address of the recipient.</p> <p>cctx - the clickable portion of the link.</p> <p>cname - the value for the NAME attribute.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<A HREF="mailto:address" NAME="cname" cattributes>cctx</A>
Example:	<p>http.mailto('pres@white_house.gov','Send Email to the President');</p> <p>generates:</p> <p>&lt;A HREF="mailto:pres@white_house.gov"&gt;Send Email to the President&lt;/A&gt;</p>

## 1.61 http.mapOpen, http.mapClose

This generates the <MAP> and </MAP> tags, which mark a set of regions in a client-side image map.

**Table 1–60** *http.mapOpen, http.mapClose*

Properties	Definitions
Syntax:	<pre> http.mapOpen(     cname          in          varchar2     cattributes     in          varchar2  DEFAULT NULL); htf.mapOpen(cname, cattributes) return varchar2;  http.mapClose; htf.mapClose return varchar2; </pre>
Parameters:	<p>cname - the value for the NAME attribute.</p> <p>cattributes - other attributes to be included as-is in the tag</p>
Generates:	<p>&lt;MAP NAME="cname" cattributes&gt;</p> <p>&lt;/MAP&gt;</p>

## 1.62 http.menuListOpen, http.menuListClose

This generates the <MENU> and </MENU> tags, which create a list that presents one line per item. The items in the list appear more compact than an unordered list. The http.listItem defines the list items in a menu list.

**Table 1–61** *htp.menuListOpen, htp.menuListClose*

Properties	Definitions
Syntax:	<pre>htp.menuListOpen; htf.menuListOpen return varchar2;  htp.menuListClose; htf.menuListClose return varchar2;</pre>
Parameters:	None.
Generates:	<pre>&lt;MENU&gt;  &lt;/MENU&gt;</pre>

---

## 1.63 htp.meta

This generates the <META> tag, which embeds meta-information about the document and also specifies values for HTTP headers. For example, you specify the expiration date, keywords, and author name.

**Table 1–62** *htp.meta*

Properties	Definitions
Syntax:	<pre>htp.meta (   chttp_equiv   in   varchar2   cname         in   varchar2   ccontent      in   varchar2); htf.meta (chttp_equiv, cname, ccontent) return varchar2;</pre>
Parameters:	<p>chttp_equiv - the value for the HTTP-EQUIV attribute.</p> <p>cname - the value for the NAME attribute.</p> <p>ccontent - the value for the CONTENT attribute.</p>
Generates:	<META HTTP-EQUIV=" <i>chttp_equiv</i> " NAME =" <i>cname</i> " CONTENT=" <i>ccontent</i> ">
Example:	<pre>htp.meta ('Refresh', NULL, 120); generates: &lt;META HTTP-EQUIV="Refresh" CONTENT=120&gt;</pre> <p>On some Web browsers, this causes the current URL to be reloaded automatically every 120 seconds.</p>

---



## 1.64 htp.nl, htp.br

This generates the <BR> tag, which begins a new line of text.

**Table 1–63** *htp.nl, htp.br*

Properties	Definitions
Syntax:	<pre> htp.nl (     cclear          in          varchar2  DEFAULT NULL     cattributes     in          varchar2  DEFAULT NULL); htf.nl (cclear, cattributes) return varchar2;  htp.br (     cclear          in          varchar2  DEFAULT NULL     cattributes     in          varchar2  DEFAULT NULL); htf.br (cclear, cattributes) return varchar2; </pre>
Parameters:	<p>cclear - the value for the CLEAR attribute.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<BR CLEAR="cclear" cattributes>

## 1.65 htp.nobr

This generates the <NOBR> and </NOBR> tags, which turn off line-breaking in a section of text.

**Table 1–64** *htp.nobr*

Properties	Definitions
Syntax:	<pre> htp.nobr(ctext in varchar2); htf.nobr(ctext) return varchar2; </pre>
Parameters:	ctext - the text that is to be rendered on one line.
Generates:	<NOBR>ctext</NOBR>

## 1.66 htp.noframesOpen, htp.noframesClose

This generates the <NOFRAMES> and </NOFRAMES> tags, which mark a no-frames section.

**Table 1–65** *http.noframesOpen, http.noframesClose*

Properties	Definitions
Syntax:	<pre> http.noframesOpen htf.noframesOpen return varchar2;  http.noframesClose htf.noframesClose return varchar2; </pre>
Parameters:	None.
Generates:	<pre> &lt;NOFRAMES&gt;  &lt;/NOFRAMES&gt; </pre>
See Also:	http.frame, http.framesetOpen, http.framesetClose

## 1.67 http.olistOpen, http.olistClose

This generates the <OL> and </OL> tags, which define an ordered list. An ordered list presents a list of numbered items. Numbered items are added using http.listItem.

**Table 1–66** *http.olistOpen, http.olistClose*

Properties	Definitions
Syntax:	<pre> http.olistOpen (   cclear      in      varchar2  DEFAULT NULL   cwrap       in      varchar2  DEFAULT NULL   cattributes in      varchar2  DEFAULT NULL); htf.olistOpen (cclear, cwrap, cattributes) return varchar2;  http.olistClose; htf.olistClose return varchar2; </pre>
Parameters:	<p>cclear - the value for the CLEAR attribute.</p> <p>cwrap - the value for the WRAP attribute.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<pre> &lt;OL CLEAR="cclear" WRAP="cwrap" cattributes&gt;  &lt;/OL&gt; </pre>

## 1.68 htp.para, htp.paragraph

This generates the <P> tag, which indicates that the text that comes after the tag is to be formatted as a paragraph. `htp.paragraph` enables you to add attributes to the tag.

**Table 1–67** *htp.para, htp.paragraph*

Properties	Definitions
Syntax:	<pre> htp.para; htf.para return varcahr2;  htp.paragraph (     calign          in          varchar2  DEFAULT NULL     cnowrap        in          varchar2  DEFAULT NULL     cclear         in          varchar2  DEFAULT NULL     cattributes    in          varchar2  DEFAULT NULL); htf.paragraph (calign, cnowrap, cclear, cattributes) return varchar2; </pre>
Parameters:	<p><code>calign</code> - the value for the ALIGN attribute.</p> <p><code>cnowrap</code> - if the value for this parameter is not NULL, the NOWRAP attribute is added to the tag.</p> <p><code>cclear</code> - the value for the CLEAR attribute.</p> <p><code>cattributes</code> - other attributes to be included as-is in the tag.</p>
Generates:	<pre> &lt;P&gt;  &lt;P ALIGN="<i>calign</i>" NOWRAP CLEAR="<i>cclear</i>" <i>cattributes</i>&gt; </pre>

## 1.69 htp.param

This generates the <PARAM> tag, which specifies parameter values for Java applets. The values can reference HTML variables. To invoke a Java applet from a Web page, use `htp.appletopen` to begin the invocation. Use one `htp.param` for each desired name-value pair, and use `htp.appletclose` to end the applet invocation.

**Table 1–68** *htp.param*

Properties	Definitions
Syntax:	<pre>htp.param(     cname          in          varchar2     cvalue         in          varchar2); htf.param(cname, cvalue) return varchar2;</pre>
Parameters:	<p>cname - the value for the NAME attribute.</p> <p>cvalue - the value for the VALUE attribute.</p>
Generates:	<PARAM NAME= <i>cname</i> VALUE=" <i>cvalue</i> ">

## 1.70 htp.plaintext

This generates the <PLAINTEXT> and </PLAINTEXT> tags, which direct the browser to render the text they surround in fixed-width type.

**Table 1–69** *htp.plaintext*

Properties	Definitions
Syntax:	<pre>htp.plaintext(     ctext          in          varchar2     cattributes    in          varchar2  DEFAULT NULL); htf.plaintext(ctext, cattributes) return varchar2;</pre>
Parameters:	<p>ctext - the text to be rendered in fixed-width font.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<PLAINTEXT <i>cattributes</i> > <i>ctext</i> </PLAINTEXT>

## 1.71 htp.preOpen, htp.preClose

This generates the <PRE> and </PRE> tags, which mark a section of preformatted text in the body of the HTML page.

**Table 1–70** *http.preOpen, http.preClose*

Properties	Definitions
Syntax:	<pre> http.preOpen (     cclear          in      varchar2  DEFAULT NULL     cwidth          in      varchar2  DEFAULT NULL     cattributes     in      varchar2  DEFAULT NULL); htf.preOpen (cclear, cwidth, cattributes) return varchar2;  http.preClose; htf.preClose return varchar2; </pre>
Parameters:	<p>cclear - the value for the CLEAR attribute.</p> <p>cwidth - the value for the WIDTH attribute.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<pre> &lt;PRE CLEAR="cclear" WIDTH="cwidth" cattributes&gt; &lt;/PRE&gt; </pre>

## 1.72 http.print, http.prn

`http.print` generates the specified parameter as a string terminated with the `\n` newline character. The `\n` character is not the same as `<BR>`. The `\n` character formats the HTML source; it does not affect how the browser renders the HTML source. Use `<BR>` to control how the browser renders the HTML source.

`http.prn` generates the specified parameter as a string. Unlike `http.print`, the string is not terminated with the `\n` newline character. These subprograms are procedures only, they do not come as functions.

**Table 1–71** *htp.print, htp.prn*

Properties	Definitions
Syntax	<pre>htp.print (cbuf in varchar2); htp.print (dbuf in date); htp.print (nbuf in number);  htp.prn (cbuf in varchar2); htp.prn (dbuf in date); htp.prn (nbuf in number);</pre>
Parameters:	cbuf, dbuf, nbuf - the string to generate.
Generates:	<p>htp.print - a string terminated with a newline.</p> <p>htp.prn - the specified string, not terminated with a newline.</p>

## 1.73 htp.prints, htp.ps

Both these subprograms generate a string and replace the following characters with the corresponding escape sequence.

- < to &lt;
- > to &gt;
- " to &quot;
- & to &amp;

If not replaced, the special characters are interpreted as HTML control characters and produce garbled output. This procedure is the same as `htp.prn` but with the character substitution. These subprograms are procedures only, they are not available as functions. Use `htf.escape_sc` if you need a string conversion function.

**Table 1–72** *htp.prints, htp.ps*

Properties	Definitions
Syntax:	<pre>htp.prints(ctext in varchar2); htp.ps(ctext in varchar2);</pre>
Parameters:	ctext - the string where to perform character substitution.
Generates:	A string.

## 1.74 htp.s

This generates the `<S>` and `</S>` tags, which direct the browser to render the text they surround in strikethrough type.

**Table 1–73** *htp.s*

Properties	Definitions
Syntax:	<pre>htp.s(     ctext          in          varchar2     cattributes    in          varchar2  DEFAULT NULL); htf.s(ctext, cattributes) return varchar2;</pre>
Parameters:	<p>ctext - the text to render in strikethrough type.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<S <i>cattributes</i> >ctext</S>

## 1.75 htp.sample

This generates the <SAMP> and </SAMP> tags, which direct the browser to render the text they surround in monospace font.

**Table 1–74** *htp.sample*

Properties	Definitions
Syntax:	<pre>htp.sample (     ctext          in          varchar2     cattributes    in          varchar2  DEFAULT NULL); htf.sample (ctext, cattributes) return varchar2;</pre>
Parameters:	<p>ctext - the text to render in monospace font.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<SAMP <i>cattributes</i> >ctext</SAMP>

## 1.76 htp.script

This generates the <SCRIPT> and </SCRIPT> tags, which contain a script written in languages such as JavaScript and VBscript.

**Table 1–75** *htp.script*

Properties	Definitions
Syntax:	<pre>htp.script(     cscript          in          varchar2     clanguage        in          varchar2  DEFAULT NULL); htf.script(cscript, clanguage) return varchar2;</pre>
Parameters:	<p>cscript - the text of the script. This is the text that makes up the script itself, not the name of a file containing the script.</p> <p>clanguage - the language in which the script is written. If this parameter is omitted, the user's browser determines the scripting language.</p>
Generates:	<code>&lt;SCRIPT LANGUAGE=<i>clanguage</i>&gt;<i>cscript</i>&lt;/SCRIPT&gt;</code>
Example:	<pre>htp.script ('Erupting_Volcano', 'Javascript');</pre> <p>generates:</p> <pre>&lt;SCRIPT LANGUAGE=Javascript&gt;"script text here" &lt;/SCRIPT&gt;</pre> <p>This causes the browser to run the script enclosed in the tags.</p>

---

## 1.77 htp.small

This generates the `<SMALL>` and `</SMALL>` tags, which direct the browser to render the text they surround using a small font.

**Table 1–76** *htp.small*

Properties	Definitions
Syntax:	<pre>htp.small(     ctext           in          varchar2     cattributes     in          varchar2  DEFAULT NULL); htf.small(ctext, cattributes) return varchar2;</pre>
Parameters:	<p>ctext - the text to render in a small font.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<code>&lt;SMALL <i>cattributes</i>&gt;<i>ctext</i>&lt;/SMALL&gt;</code>

---

## 1.78 htp.strike

This generates the `<STRIKE>` and `</STRIKE>` tags, which direct the browser to render the text they surround in strikethrough type.



**Table 1–77** *htp.strike*

Properties	Definitions
Syntax:	<pre>htp.strike(     ctext          in          varchar2     cattributes    in          varchar2  DEFAULT NULL); htf.strike(ctext, cattributes) return varchar2;</pre>
Parameters:	<p>ctext - the text to be rendered in strikethrough type.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<STRIKE <i>cattributes</i> >ctext</STRIKE>

## 1.79 htp.strong

This generates the <STRONG> and </STRONG> tags, which direct the browser to render the text they surround in bold.

**Table 1–78** *htp.strong*

Properties	Definitions
Syntax:	<pre>htp.strong (     ctext          in          varchar2     cattributes    in          varchar2  DEFAULT NULL); htf.strong (ctext, cattributes) return varchar2;</pre>
Parameters:	<p>ctext - the text to be emphasized.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<STRONG <i>cattributes</i> >ctext</STRONG>

## 1.80 htp.style

This generates the <STYLE> and </STYLE> tags, which include a style sheet in your Web page. Style sheets are a feature of HTML 3.2. You can get more information about style sheets at <http://www.w3.org>. This feature is not compatible with browsers that support only HTML versions 2.0 or earlier. Such browsers will ignore this tag.

**Table 1–79** *htp.style*

Properties	Definitions
Syntax:	htp.style(cstyle in varchar2); htf.style(cstyle) return varchar2;
Parameters:	cstyle - the style information to include.
Generates:	<STYLE>cstyle</STYLE>

## 1.81 htp.sub

This generates the <SUB> and </SUB> tags, which direct the browser to render the text they surround as subscript.

**Table 1–80** *htp.sub*

Properties	Definitions
Syntax:	htp.sub( ctext                in          varchar2 calign              in          varchar2  DEFAULT NULL cattributes        in          varchar2  DEFAULT NULL); htf.sub(ctext, calign, cattributes) return varchar2;
Parameters:	ctext - the text to render in subscript. calign - the value for the ALIGN attribute. cattributes - other attributes to be included as-is in the tag.
Generates:	<SUB ALIGN=" <i>calign</i> " <i>cattributes</i> >ctext</SUB>

## 1.82 htp.sup

This generates the <SUP> and </SUP> tags, which direct the browser to render the text they surround as superscript.

**Table 1–81** *htp.sup*

Properties	Definitions
Syntax:	<pre>htp.sup(     ctext          in          varchar2     calign         in          varchar2  DEFAULT NULL     cattributes   in          varchar2  DEFAULT NULL); htf.sup(ctext, calign, cattributes) return varchar2;</pre>
Parameters:	<p>ctext - the text to render in subscript.  calign - the value for the ALIGN attribute.  cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<SUP ALIGN=" <i>calign</i> " <i>cattributes</i> > <i>ctext</i> </SUP>

## 1.83 htp.tableCaption

This generates the <CAPTION> and </CAPTION> tags, which place a caption in an HTML table.

**Table 1–82** *htp.tableCaption*

Properties	Definitions
Syntax:	<pre>htp.tableCaption (     ccaption      in          varchar2     calign       in          varchar2  DEFAULT NULL     cattributes  in          varchar2  DEFAULT NULL); htf.tableCaption (ccaption, calign, cattributes) return varchar2;</pre>
Parameters:	<p>ccaption - the text for the caption.  calign - the value for the ALIGN attribute.  cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<CAPTION ALIGN=" <i>calign</i> " <i>cattributes</i> > <i>ccaption</i> </CAPTION>

## 1.84 htp.tableData

This generates the <TD> and </TD> tags, which insert data into a cell of an HTML table.

**Table 1–83** *htp.tableData*

Properties	Definitions
Syntax:	<pre> htp.tableData (     cvalue          in          varchar2  DEFAULT NULL     calign          in          varchar2  DEFAULT NULL     cdp             in          varchar2  DEFAULT NULL     cnowrap        in          varchar2  DEFAULT NULL     crowspan       in          varchar2  DEFAULT NULL     ccolspan       in          varchar2  DEFAULT NULL     cattributes    in          varchar2  DEFAULT NULL); htf.tableData (cvalue, calign, cdp, cnowrap, crowspan, ccolspan, cattributes) return varchar2; </pre>
Parameters:	<p>cvalue - the data for the cell in the table.</p> <p>calign - the value for the ALIGN attribute.</p> <p>cdp - the value for the DP attribute.</p> <p>cnowrap - if the value of this parameter is not NULL, the NOWRAP attribute is added to the tag.</p> <p>crowspan - the value for the ROWSPAN attribute.</p> <p>ccolspan - the value for the COLSPAN attribute.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<pre> &lt;TD ALIGN="<i>calign</i>" DP="<i>cdp</i>" ROWSPAN="<i>crowspan</i>" COLSPAN="<i>ccolspan</i>" NOWRAP <i>cattributes</i>&gt;<i>cvalue</i>&lt;/TD&gt; </pre>

## 1.85 htp.tableHeader

This generates the <TH> and </TH> tags, which insert a header cell in an HTML table. The <TH> tag is similar to the <TD> tag, except that the text in the rows are usually rendered in bold type.

**Table 1–84** *http.tableHeader*

Properties	Definitions
Syntax:	<pre> http.tableHeader (     cvalue      in      varchar2  DEFAULT NULL     calign      in      varchar2  DEFAULT NULL     cdp         in      varchar2  DEFAULT NULL     cnowrap     in      varchar2  DEFAULT NULL     crowspan    in      varchar2  DEFAULT NULL     ccolspan    in      varchar2  DEFAULT NULL     cattributes in      varchar2  DEFAULT NULL); htf.tableHeader (cvalue, calign, cdp, cnowrap, crowspan, ccolspan, cattributes) return varchar2; </pre>
Parameters:	<p>cvalue - the data for the cell in the table.</p> <p>calign - the value for the ALIGN attribute.</p> <p>cdp - the value for the DP attribute.</p> <p>cnowrap - if the value of this parameter is not NULL, the NOWRAP attribute is added to the tag.</p> <p>crowspan - the value for the ROWSPAN attribute.</p> <p>ccolspan - the value for the COLSPAN attribute.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<pre> &lt;TH ALIGN="<i>calign</i>" DP="<i>cdp</i>" ROWSPAN="<i>crowspan</i>" COLSPAN="<i>ccolspan</i>" NOWRAP <i>cattributes</i>&gt;<i>cvalue</i>&lt;/TH&gt; </pre>

## 1.86 http.tableOpen, http.tableClose

This generates the <TABLE> and </TABLE> tags, which define an HTML table.

**Table 1–85** *htp.tableOpen, htp.tableClose*

Properties	Definitions
Syntax:	<pre> htp.tableOpen (     cborder      in      varchar2  DEFAULT NULL     calign       in      varchar2  DEFAULT NULL     cnowrap     in      varchar2  DEFAULT NULL     cclear       in      varchar2  DEFAULT NULL     cattributes  in      varchar2  DEFAULT NULL); htf.tableOpen (cborder, calign, cnowrap, cclear, cattributes) return varchar2;  htp.tableClose; htf.tableClose return varchar2; </pre>
Parameters:	<p><b>cborder</b> - the value for the BORDER attribute.</p> <p><b>calign</b> - the value for the ALIGN attribute.</p> <p><b>cnowrap</b> - if the value of this parameter is not NULL, the NOWRAP attribute is added to the tag.</p> <p><b>cclear</b> - the value for the CLEAR attribute.</p> <p><b>cattributes</b> - other attributes to be included as-is in the tag.</p>
Generates:	<pre> &lt;TABLE "<i>cborder</i>" NOWRAP ALIGN="<i>calign</i>" CLEAR="<i>cclear</i>" <i>cattributes</i>&gt; &lt;/TABLE&gt; </pre>

---

## 1.87 htp.tableRowOpen, htp.tableRowClose

This generates the <TR> and </TR> tags, which inserts a new row in an HTML table.

**Table 1–86** *htp.tableRowOpen, htp.tableRowClose*

Properties	Definitions
Syntax:	<pre> htp.tableRowOpen (     calign      in      varchar2  DEFAULT NULL     cvalign     in      varchar2  DEFAULT NULL     cdp         in      varchar2  DEFAULT NULL     cnowrap    in      varchar2  DEFAULT NULL     cattributes in      varchar2  DEFAULT NULL); htf.tableRowOpen (calign, cvalign,cdp, cnowrap, cattributes) return varchar2;  htp.tableRowClose; htp.tableRowClose return varchar2; </pre>
Parameters:	<p><i>calign</i> - the value for the ALIGN attribute.</p> <p><i>cvalign</i> - the value for the VALIGN attribute.</p> <p><i>cdp</i> - the value for the DP attribute.</p> <p><i>cnowrap</i> - if the value of this parameter is not NULL, the NOWRAP attribute is added to the tag.</p> <p><i>cattributes</i> - other attributes to be included as-is in the tag.</p>
Generates:	<pre> &lt;TR ALIGN="<i>calign</i>" VALIGN="<i>cvalign</i>" DP="<i>cdp</i>" NOWRAP <i>cattributes</i>&gt; &lt;/TR&gt; </pre>

## 1.88 htp.teletype

This generates the <TT> and </TT> tags, which direct the browser to render the text they surround in a fixed width typewriter font, for example, the courier font.

**Table 1–87** *htp.teletype*

Properties	Definitions
Syntax:	<pre> htp.teletype (     ctext      in      varchar2     cattributes in      varchar2  DEFAULT NULL); htf.teletype (ctext, cattributes) return varchar2; </pre>
Parameters:	<p><i>ctext</i> - the text to render in a fixed width typewriter font.</p> <p><i>cattributes</i> - other attributes to be included as-is in the tag.</p>
Generates:	<pre> &lt;TT <i>cattributes</i>&gt;<i>ctext</i>&lt;/TT&gt; </pre>

## 1.89 htp.title

This generates the <TITLE> and </TITLE> tags, which specify the text to display in the titlebar of the browser window.

**Table 1–88** *htp.title*

Properties	Definitions
Syntax:	<pre>htp.title (ctitle in varchar2); htf.title (ctitle) return varchar2;</pre>
Parameters:	ctitle - the text to display in the titlebar of the browser window.
Generates:	<TITLE> <i>ctitle</i> </TITLE>

## 1.90 htp.ulistOpen, htp.ulistClose

This generates the <UL> and </UL> tags, which define an unordered list. An unordered list presents items with bullets. Add list items with htp.listItem.

**Table 1–89** *htp.ulistOpen, htp.ulistClose*

Properties	Definitions
Syntax:	<pre>htp.ulistOpen (     cclear          in          varchar2  DEFAULT NULL     cwrap           in          varchar2  DEFAULT NULL     cdingbat        in          varchar2  DEFAULT NULL     csrc            in          varchar2  DEFAULT NULL     cattributes     in          varchar2  DEFAULT NULL htf.ulistOpen (cclear, cwrap, cdingbat, csrc, cattributes) return varchar2;  htp.ulistClose; htf.ulistClose return varhar2;</pre>
Parameters:	<p>cclear - the value for the CLEAR attribute.</p> <p>cwrap - the value for the WRAP attribute.</p> <p>cdingbat - the value for the DINGBAT attribute.</p> <p>csrc - the value for the SRC attribute.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<UL CLEAR=" <i>cclear</i> " WRAP=" <i>cwrap</i> " DINGBAT=" <i>cdingbat</i> " SRC=" <i>csrc</i> " <i>cattributes</i> > </UL>



## 1.91 htp.underline

This generates the <U> and </U> tags, which direct the browser to render the text they surround with an underline.

**Table 1–90** *htp.underline*

Properties	Definitions
Syntax:	<pre>htp.underline(     ctext          in          varchar2     cattributes    in          varchar2  DEFAULT NULL); htf.underline(ctext, cattributes) return varchar2;</pre>
Parameters:	<p>ctext - the text to render with an underline.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<U <i>cattributes</i> >ctext</U>

## 1.92 htp.variable

This generates the <VAR> and </VAR> tags, which direct the browser to render the text they surround in italics.

**Table 1–91** *htp.variable*

Properties	Definitions
Syntax:	<pre>htp.variable (     ctext          in          varchar2     cattributes    in          varchar2  DEFAULT NULL); htf.variable (ctext, cattributes) return varchar2;</pre>
Parameters:	<p>ctext - the text to render in italics.</p> <p>cattributes - other attributes to be included as-is in the tag.</p>
Generates:	<VAR <i>cattributes</i> >ctext</VAR>

## 1.93 htp.wbr

This generates the <WBR> tag, which inserts a soft line break within a section of NOBR text.

**Table 1–92** *http.wbr*

<b>Properties</b>	<b>Definitions</b>
Syntax:	<code>http.wbr;</code> <code>htf.wbr return wbr;</code>
Parameters:	None.
Generates:	<WBR>

---

---

# The owa\_cache Package

The owa\_cache package contains functions and procedures that enable the PL/SQL Gateway cache feature to improve the performance of your PL/SQL web application. This section describes the specification of these functions and procedures.

## 2.1 Summary

owa\_cache.disable - disables the cache for this particular request.

owa\_cache.set\_expires - sets up the cache headers for expires model cache type.

owa\_cache.set\_cache - sets up the cache headers for validation model cache type.

owa\_cache.set\_not\_modified - sets up the headers for a not modified cache hit (used in the Validation technique model only).

owa\_cache.get\_level - returns the caching level (used in the Validation technique model only).

owa\_cache.get\_etag - returns the tag associated with the cached content (used in the Validation technique model only).

## 2.2 owa\_cache.disable

This disables the cache for this particular request.

**Table 2–1 owa\_cache.disable**

Properties	Definitions
Parameters:	p_expires IN - the number of minutes this content is valid. p_level IN - the caching level for it.
Exceptions:	VALUE_ERROR is thrown if p_expires is negative or zero, or p_level is not 'USER' or 'SYSTEM', or p_expires is > 525600 (1 year).

## 2.3 owa\_cache.set\_expires

This sets up the cache headers for expires model cache type.

**Table 2–2 owa\_cache.set\_expires**

Properties	Definitions
Parameters:	p_expires IN - the number of minutes this content is valid. p_level IN - the caching level for it
Exceptions:	VALUE_ERROR is thrown if p_expires is negative or zero, or p_level is not 'USER' or 'SYSTEM', or p_expires is > 525600 (1 year).

## 2.4 owa\_cache.set\_cache

This sets up the cache headers for validation model cache type.

**Table 2–3 owa\_cache.set\_cache**

Properties	Definitions
Parameters:	p_etag IN - the tag associated with this content. p_level IN - the caching level for it.
Exceptions:	VALUE_ERROR is thrown if p_etag is greater than 55, or p_level is not 'USER' or 'SYSTEM'.

## 2.5 owa\_cache.set\_not\_modified

This sets up the headers for a not modified cache hit. It is used in the Validation technique only.

**Table 2–4** *owa\_cache.set\_not\_modified*

Properties	Definitions
Exceptions:	VALUE_ERROR is thrown if <b>ETag</b> was not passed in.

## 2.6 owa\_cache.get\_level

This returns the caching level. It is used in the Validation technique model only.

**Table 2–5** *owa\_cache.get\_level*

Properties	Definitions
Returns:	The caching level string ('USER' or 'SYSTEM') for cache hit; null otherwise.

## 2.7 owa\_cache.get\_etag

This returns the tag associated with the cached content. It is used in the Validation technique only.

**Table 2–6** *owa\_cache.get\_etag*

Properties	Definitions
Returns:	The tag for cache hit; null otherwise.



---

---

## The owa\_cookie Package

The owa\_cookie package contains subprograms that send and retrieve HTTP cookies from the client's browser. Cookies are opaque strings sent to the browser to maintain state between HTTP calls. State can be maintained throughout the client's sessions, or longer if an expiration date is included. Your system date is calculated with reference to the information specified in the owa\_custom package.

### 3.1 Summary

owa\_cookie.cookie data type - data type to contain cookie name-value pairs.

owa\_cookie.get function - gets the value of the specified cookie.

owa\_cookie.get\_all procedure - gets all cookie name-value pairs.

owa\_cookie.remove procedure - removes the specified cookie.

owa\_cookie.send procedure - generates a "Set-Cookie" line in the HTTP header.

---

---

**Note:** All HTTP headers must be in English. If the headers are generated from the database, verify they are created in the English language.

---

---

### 3.2 owa\_cookie.cookie data type

Since the HTTP standard allows cookie names to be overloaded (that is, multiple values can be associated with the same cookie name), this is a PL/SQL RECORD holding all values associated with a given cookie name.

Type vc\_arr is table of varchar2(4000) index by binary\_integer.

**Table 3–1** *owa\_cookie.cookie data type*

Properties	Definitions
Syntax:	<pre>type cookie is RECORD (     name          varchar2(4000),     vals          vc_arr,     num_vals      integer);</pre>
Returns:	Not applicable.

### 3.3 owa\_cookie.get function

This function returns the values associated with the specified cookie. The values are returned in a *owa\_cookie.cookie* data type.

**Table 3–2** *owa\_cookie.get function*

Properties	Definitions
Syntax:	<code>owa_cookie.get(name in varchar2) return cookie;</code>
Parameter:	name - the name of the cookie.
Returns:	An <i>owa_cookie.cookie</i> data type.

### 3.4 owa\_cookie.get\_all procedure

This procedure returns all cookie names and their values from the client's browser. The values appear in the order in which they were sent from the browser.

**Table 3–3** *owa\_cookie.get\_all procedures*

Properties	Definitions
Syntax:	<pre>owa_cookie.get_all(     names          out          vc_arr,     vals          out          vc_arr,     num_vals      out          integer);</pre>
Parameters:	<p>names - the names of the cookies.</p> <p>vals - the values of the cookies.</p> <p>num_vals - the number of cookie-value pairs.</p>
Generates:	Arrays of the names and values in the order received, and the count of the combinations.



## 3.5 owa\_cookie.remove procedure

This procedure forces a cookie to expire immediately by setting the "expires" field of a Set-Cookie line in the HTTP header to "01-Jan-1990". This procedure must be called within the context of an HTTP header.

**Table 3–4** *owa\_cookie.remove procedure*

Properties	Definitions
Syntax:	<pre>owa_cookie.remove(     name          in          varchar2,     val           in          varchar2,     path          in          varchar2  DEFAULT NULL);</pre>
Parameters:	<p>name - the name of the cookie to expire.</p> <p>value - the value of the cookie.</p> <p>path - currently unused.</p>
Generates:	Set-Cookie: <name>=<value> expires=01-JAN-1990

## 3.6 owa\_cookie.send procedure

This procedure generates a Set-Cookie line, which transmits a cookie to the client. This procedure must occur in the context of an HTTP header.

**Table 3–5** owa\_cookie.send procedure

Properties	Definitions
Syntax	<pre>owa_cookie.send(   name      in      varchar2,   value     in      varchar2,   expires   in      date      DEFAULT NULL,   path      in      varchar2  DEFAULT NULL,   domain    in      varchar2  DEFAULT NULL,   secure    in      varchar2  DEFAULT NULL);</pre>
Parameters:	<p>name -the name of the cookie.</p> <p>value - the value of the cookie.</p> <p>expires - the date at which the cookie will expire.</p> <p>path - the value for the path field.</p> <p>domain - the value for the domain field.</p> <p>secure - if the value of this parameter is not NULL, the "secure" field is added to the line.</p>
Generates:	<p>Set-Cookie: &lt;name&gt;=&lt;value&gt; expires=&lt;expires&gt; path=&lt;path&gt; domain=&lt;domain&gt; secure</p>

---

---

---

## The owa\_image Package

The owa\_image package contains subprograms that get the coordinates of where the user clicked on an image. Use this package when you have any image map whose destination links invoke the PL/SQL Gateway. Your procedure would look something like:

```
create or replace procedure process_image
  (my_img in owa_image.point)
as
  x integer := owa_image.get_x(my_img);
  y integer := owa_image.get_y(my_img);
begin
  /* process the coordinate */
end
```

### 4.1 Summary

owa\_image.NULL\_POINT package variable - variable of type point whose X and Y values are NULL.

owa\_image.point data type - data type to contain the X and Y values of a coordinate.

owa\_image.get\_x function - gets the X value of a point type.

owa\_image.get\_y function - gets the Y value of a point type.

### 4.2 owa\_image.NULL\_POINT package variable

This package variable of type point is used to default point parameters. Both the X and the Y fields of this variable are NULL.

**Table 4–1** *owa\_image.NULL\_POINT package variable*

Properties	Definitions
Syntax:	<code>null_point</code> - package variable
Returns:	Not applicable.

---

## 4.3 owa\_image.point data type

This data type provides the x and y coordinates of a user's click on an imagemap. It is defined as:

```
type point is table of varchar2(32767) index by binary_integer.
```

**Table 4–2** *owa\_image.point data type*

Properties	Definitions
Syntax:	<code>point</code> - data type
Returns:	Not applicable.

---

## 4.4 owa\_image.get\_x function

This function returns the X coordinate of the point where the user clicked on an image map.

**Table 4–3** *owa\_image.get\_x function*

Properties	Definitions
Syntax:	<code>owa_image.get_x(p in point)</code> return integer;
Parameter:	<code>p</code> - the point where the user clicked.
Returns:	The X coordinate as an integer.

---

## 4.5 owa\_image.get\_y function

This function returns the Y coordinate of the point where the user clicked on an image map.

**Table 4–4** *owa\_image.get\_y function*

<b>Properties</b>	<b>Definitions</b>
Syntax:	<code>owa_image.get_y(p in point) return integer;</code>
Parameters:	p - the point where the user clicked.
Returns:	The Y coordinate as an integer.

---



---

---

## The owa\_opt\_lock Package

The `owa_opt_lock` package contains subprograms that impose optimistic locking strategies, so as to prevent lost updates. It checks if the row that the user is interested in updating has been changed by someone else in the meantime.

The PL/SQL Gateway cannot use conventional database locking schemes because HTTP is a stateless protocol. The `owa_opt_lock` package gives you two ways of dealing with the lost update problem:

- The hidden fields method stores the previous values in hidden fields in the HTML page. When the user requests an update, the PL/SQL Gateway checks these values against the current state of the database. The update operation is performed only if the values match. To use this method, call the `owa_opt_lock.store_values` procedure.
- The checksum method stores a checksum rather than the values themselves. To use this method, call the `owa_opt_lock.checksum` function.

These methods are optimistic. They do not prevent other users from performing updates, but they do reject the current update if an intervening update has occurred.

### 5.1 Summary

`owa_opt_lock.vcArray` data type - data type to contain ROWIDs.

`owa_opt_lock.checksum` function - returns the checksum value.

`owa_opt_lock.get_rowid` function - returns the ROWID value.

`owa_opt_lock.store_values` procedure - stores unmodified values in hidden fields for later verification.

owa\_opt\_lock.verify\_values function - verifies the stored values against modified values.

## 5.2 owa\_opt\_lock.vcArray data type

This data type is a PL/SQL table intended to hold ROWIDs.

Type vcArray is table of varchar2(2000) index by binary\_integer.

Note that this is different from the owa\_text.vc\_arr data type.

**Table 5–1** owa\_opt\_lock.vcArray data type

Properties	Definitions
Syntax:	owa_opt_lock.vcArray - data type
Returns:	Not applicable.

## 5.3 owa\_opt\_lock.checksum function

This function returns a checksum value for a specified string, or for a row in a table. For a row in a table, the function calculates the checksum value based on the values of the columns in the row. This function comes in two versions.

The first version returns a checksum based on the specified string. This is a "pure" 32-bit checksum executed by the database and based on the Internet 1 protocol.

The second version returns a checksum based on the values of a row in a table. This is a "impure" 32-bit checksum based on the Internet 1 protocol.



**Table 5–2** *owa\_opt\_lock.checksum function*

Properties	Definitions
Syntax:	<pre>owa_opt_lock.checksum(p_buff in varchar2) return number; owa_opt_lock.checksum(     p_owner      in      varchar2     p_tname      in      varchar2     p_rowid      in      rowid) return number;</pre>
Parameters:	<p><code>p_buff</code> - the string where you want to calculate the checksum.</p> <p><code>p_owner</code> - the owner of the table.</p> <p><code>p_tname</code> - the table name.</p> <p><code>p_rowid</code> - the row in <code>p_tname</code> where you want to calculate the checksum value. Use the <code>owa_opt_lock.get_rowid</code> function to convert vcArray values to proper rowids.</p>
Returns:	A checksum value.

## 5.4 owa\_opt\_lock.get\_rowid function

This function returns the ROWID data type from the specified `owa_opt_lock.vcArray` data type.

**Table 5–3** *owa\_opt\_lock.get\_rowid function*

Properties	Definitions
Syntax:	<pre>owa_opt_lock.get_rowid(p_old_values in vcArray) return rowid;</pre>
Parameters:	<code>p_old_values</code> - this parameter is usually passed in from an HTML form.
Returns:	A ROWID.

## 5.5 owa\_opt\_lock.store\_values procedure

This procedure stores the column values of the row that you want to update later. The values are stored in hidden HTML form elements. Before updating the row, compare these values with the current row values to ensure that the values in the row have not been changed. If the values have changed, you can warn the users and let them decide if the update should take place.

**Table 5–4** owa\_opt\_lock.store\_values procedure

Properties	Definitions
Syntax:	<pre>owa_opt_lock.store_values(     p_owner      in      varchar2     p_tname      in      varchar2     p_rowid      in      rowid);</pre>
Parameters:	<p>p_owner - the owner of the table.</p> <p>p_tname - the name of the table.</p> <p>p_rowid - the row where you want to store values.</p>
Generates:	<p>A series of hidden form elements:</p> <p>One hidden form element is created for the table owner. The name of the element is "old_p_tname", where p_tname is the name of the table. The value of the element is the owner name.</p> <p>One hidden form element is created for the table name. The name of the element is "old_p_tname", where p_tname is the name of the table. The value of the element is the table name.</p> <p>One element is created for each column in the row. The name of the element is "old_p_tname", where p_tname is the name of the table. The value of the element is the column value.</p>
See also:	owa_opt_lock.verify_values function.

---

## 5.6 owa\_opt\_lock.verify\_values function

This function verifies whether values in the specified row have been updated since the last query. Use this function with the owa\_opt\_lock.store\_values procedure.

**Table 5–5** *owa\_opt\_lock.verify\_values function*

<b>Properties</b>	<b>Definitions</b>
Syntax:	<code>owa_opt_lock.verify_values(p_old_values in vcArray) return boolean;</code>
Parameters:	<p><code>p_old_values</code> - a PL/SQL table containing the following information:</p> <p><code>p_old_values(1)</code> specifies the owner of the table. <code>p_old_values(2)</code> specifies the table. <code>p_old_values(3)</code> specifies the rowid of the row to verify. The remaining indexes contain values for the columns in the table.</p> <p>Typically, this parameter is passed in from the HTML form, where you have previously called the <code>owa_opt_lock.store_values</code> procedure to store the row values on hidden form elements.</p>
Returns:	TRUE if no other update has been performed; otherwise, FALSE.
See also:	<code>owa_opt_lock.store_values</code> procedure.



---

---

# The owa\_pattern Package

The `owa_pattern` package in the PL/SQL Web Toolkit locates text patterns within strings and replaces the matched string with another string. Use regular expressions with the subprograms in this package.

## 6.1 Subprograms

Regular Expressions - this section describes the special characters, quantifiers, and flags used in forming regular expressions.

`owa_pattern.amatch` function - determines if a string contains the specified pattern. It lets you specify where in the string the match has to occur.

`owa_pattern.change` function and procedure - replaces a pattern within a string. If you call it as a function it returns the number of times the regular expression was found and replaced.

`owa_pattern.getpat` procedure - generates a pattern data type from a VARCHAR2 type.

`owa_pattern.match` function - determines if a string contains the specified pattern.

`owa_pattern.pattern` data type - data type to store regular expressions.

These subprograms are overloaded. That is, there are several versions of each, distinguished by the parameters they use. Specifically, there are six versions of `MATCH`, and four each of `AMATCH` and `CHANGE`. The subprograms use the following parameters:

- `line` - This is the target to be examined for a match. It can be more than one line of text or a `owa_text.multi_line` data type.

- `pat` - This is the pattern that the subprograms attempt to locate in line. The pattern can contain regular expressions. In the `owa_pattern.change` function and procedure, this parameter is called `from_str`.
- `flags` - This specifies whether the search is case-sensitive or if substitutions are done globally.

## 6.2 Regular Expressions

Specify a regular expression by creating the string you want to match interspersed with various wildcard tokens and quantifiers.

### 6.2.1 Wildcard Tokens

Wildcard tokens match something other than themselves:

**Table 6–1** *Wildcard tokens recognized by owa\_pattern package*

Token	Description
<code>^</code>	Matches newline or the beginning of the target
<code>\$</code>	Matches newline or the end of the target
<code>\n</code>	Matches newline
<code>.</code>	Matches any character except newline
<code>\t</code>	Matches tab
<code>\d</code>	Matches digits [0-9]
<code>\D</code>	Matches non-digits [not 0-9]
<code>\w</code>	Matches word characters (0-9, a-z, A-Z, or <code>_</code> )
<code>\W</code>	Matches non-word characters (not 0-9, a-z, A-Z, or <code>_</code> )
<code>\s</code>	Matches whitespace characters (blank, tab, or newline).
<code>\S</code>	Matches non-whitespace characters (not blank, tab, or newline)
<code>\b</code>	Matches "word" boundaries (between <code>\w</code> and <code>\W</code> )
<code>\x&lt;HEX&gt;</code>	Matches the value in the current character set of the two hexadecimal digits
<code>\&lt;OCT&gt;</code>	Matches the value in the current character set of the two or three octal digits
<code>\</code>	Followed by any character not covered by another case matches that character

**Table 6–1 Wildcard tokens recognized by owa\_pattern package**

Token	Description
&	Applies only to CHANGE. This causes the string that matched the regular expression to be included in the string that replaces it. This differs from the other tokens in that it specifies how a target is changed rather than how it is matched. This is explained further under CHANGE.

## 6.2.2 Quantifiers

Any tokens except & can have their meaning extended by any of the following quantifiers. You can also apply these quantifiers to literals:

**Table 6–2 Quantifiers**

Quantifier	Description
?	0 or 1 occurrence(s)
*	0 or more occurrences
+	1 or more occurrence(s)
{n}	Exactly <i>n</i> occurrences
{n, }	At least <i>n</i> occurrences
{n, m}	At least <i>n</i> , but not more than <i>m</i> , occurrences

## 6.2.3 Flags

In addition to targets and regular expressions, the owa\_pattern functions and procedures use flags to affect how they are interpreted.

**Table 6–3 Flags**

Flag	Description
i	This indicates a case-insensitive search.
g	This applies only to CHANGE. It indicates a global replace. That is, all portions of the target that match the regular expression are replaced.

## 6.3 owa\_pattern.amatch function

This function specifies if a pattern occurs in a particular location in a string. There are four versions to this function:

- The first and second versions of the function do not save the matched tokens (these are saved in the *backrefs* parameters in the third and fourth versions). The difference between the first and second versions is the *pat* parameter, which can be a VARCHAR2 or a pattern data type.
- The third and fourth versions of the function save the matched tokens in the *backrefs* parameter. The difference between the third and fourth versions is the *pat* parameter, which can be a VARCHAR2 or a pattern data type.

---



---

**Note:** If multiple overlapping strings match the regular expression, this function takes the longest match.

---



---

**Table 6–4** owa\_pattern.amatch function

Properties	Definitions
Syntax:	<pre> owa_pattern.amatch(   line          in          varchar2   from_loc      in          integer   pat           in          varchar2   flags        in          varchar2  DEFAULT NULL) return integer;  owa_pattern.amatch(   line          in          varchar2   from_loc      in          integer   pat           in out     pattern   flags        in          varchar2  DEFAULT NULL) return integer;  owa_pattern.amatch(   line          in          varchar2   from_loc      in          integer   pat           in          varchar2   backrefs     out         owa_text.vc_arr   flags        in          varchar2  DEFAULT NULL) return integer; </pre>



**Table 6–4** *owa\_pattern.amatch* function

Properties	Definitions
	<pre>owa_pattern.amatch(   line      in      varchar2   from_loc  in      integer   pat       in out  pattern   backrefs  out     owa_text.vc_arr   flags     in      varchar2  DEFAULT NULL) return integer;</pre>
Parameters:	<p><b>line</b> - the text to search in.</p> <p><b>from_loc</b> - the location (in number of characters) in <i>line</i> where the search is to begin.</p> <p><b>pat</b> - the string to match. It can contain regular expressions. This can be either a VARCHAR2 or a pattern. If it is a pattern, the output value of this parameter is the pattern matched.</p> <p><b>backrefs</b> - the text that is matched. Each token that is matched is placed in a cell in the owa_text.vc_arr data type PL/SQL table.</p> <p><b>flags</b> - whether or not the search is case-sensitive. If the value of this parameter is "i", the search is case-insensitive. Otherwise the search is case-sensitive.</p>
Returns:	<p>The index of the character after the end of the match, counting from the beginning of <i>line</i>. If there was no match, the function returns 0.</p>

## 6.4 owa\_pattern.change function and procedure

This function or procedure searches and replaces a string or multi\_line data type. If multiple overlapping strings match the regular expression, this function takes the longest match.

**Table 6–5** *owa\_pattern.change function and procedure*

Properties	Definitions
Syntax:	<pre> /* function */ owa_pattern.change(   line      in out  varchar2   from_str  in      varchar2   to_str    in      varchar2   flags     in      varchar2  DEFAULT NULL) return integer;  /* procedure */ owa_pattern.change(   line      in out  varchar2   from_str  in      varchar2   to_str    in      varchar2   flags     in      varchar2  DEFAULT NULL);  /* function */ owa_pattern.change(   mline     in out  owa_text.multi_line   from_str  in      varchar2   to_str    in      varchar2   flags     in      varchar2  DEFAULT NULL) return integer;  /* procedure */ owa_pattern.change(   mline     in out  owa_text.multi_line   from_str  in      varchar2   to_str    in      varchar2   flags     in      varchar2  DEFAULT NULL); </pre>

**Table 6–5** *owa\_pattern.change function and procedure*

Properties	Definitions
Parameters:	<p>line - the text to search in. The output value of this parameter is the altered string.</p> <p>mline - the text to search in. This is a owa_text.multi_line data type data type. The output value of this parameter is the altered string.</p> <p>from_str - the regular expression to replace.</p> <p>to_str - the substitution pattern.</p> <p>flags - whether or not the search is case-sensitive, and whether or not changes are to be made globally. If "i" is specified, the search is case-insensitive. If "g" is specified, changes are made to all matches. Otherwise, the function stops after the first substitution is made.</p>
Returns:	As a function, it returns the number of substitutions made. If the flag 'g' is not used, this number can only be 0 or 1 and only the first match is replaced. The flag 'g' specifies to replace all matches with the regular expression.
Example:	<p>Example 1:</p> <pre>owa_pattern.change('Cats in pajamas', 'C.+in', '&amp; red ')</pre> <p>The regular expression matches the substring 'Cats in'. It then replaces this string with '&amp; red'. The ampersand character (&amp;) indicates 'Cats in', since that's what matched the regular expression. Thus, this procedure replaces the string 'Cats in pajamas' with 'Cats in red'. If you called this as a function instead of a procedure, the value it returns is 1, indicating that a single substitution has been made.</p> <p>Example 2:</p> <pre>create or replace procedure test_pattern as theline VARCHAR2(256);   num_found integer; begin   theline := 'what is the goal?';   num_found := owa_pattern.change(theline, 'goal', 'idea', 'g');   htp.print(num_found); -- num_found is 1   htp.print(theline); -- theline is 'what is the idea?' end; / show errors</pre>

## 6.5 owa\_pattern.getpat procedure

This procedure converts a VARCHAR2 string into a owa\_pattern.pattern data type.

**Table 6–6** *owa\_pattern.getpat procedure*

Properties	Definitions
Syntax:	<code>owa_pattern.getpat(arg in VARCHAR2, pat in out pattern);</code>
Parameters:	<code>arg</code> - the string to convert. <code>pat</code> - the <code>owa_pattern.pattern</code> data type initialized with <code>arg</code> .
Returns:	None.

## 6.6 owa\_pattern.match function

This function determines if a string contains the specified pattern. The pattern can contain regular expressions. If multiple overlapping strings can match the regular expression, this function takes the longest match.

The regular expression in this function can be either a `VARCHAR2` or a `owa_pattern.pattern` data type. Create a `owa_pattern.pattern` data type from a string using the `owa_pattern.getpat` procedure.

Create a `multi_line` data type from a long string using the `owa_text.stream2multi` procedure. If a `multi_line` is used, the `rlist` parameter specifies a list of chunks where matches were found.

If the line is a string and not a `multi_line`, you can add an optional output parameter called `backrefs`. This parameter is a `row_list` that holds each string in the target that was matched by a sequence of tokens in the regular expression.

**Table 6–7** *owa\_pattern.match* function

Properties	Definitions
Syntax:	<pre> owa_pattern.match(   line      in      varchar2   pat       in      varchar2   flags     in      varchar2  DEFAULT NULL) return boolean;  owa_pattern.match(   line      in      varchar2   pat       in out   pattern   flags     in      varchar2  DEFAULT NULL) return boolean;  owa_pattern.match(   line      in      varchar2   pat       in      varchar2   backrefs  out     owa_text.vc_arr   flags     in      varchar2  DEFAULT NULL) return boolean;  owa_pattern.match(   line      in      varchar2   pat       in out   pattern   backrefs  out     owa_text.vc_arr   flags     in      varchar2  DEFAULT NULL) return boolean;  owa_pattern.match(   mline     in      owa_text.multi_line   pat       in      varchar2   rlist     out     owa_text.row_list   flags     in      varchar2  DEFAULT NULL) return boolean;  owa_pattern.match(   mline     in      owa_text.multi_line   pat       in out   pattern   rlist     out     owa_text.row_list   flags     in      varchar2  DEFAULT NULL) return boolean; </pre>

**Table 6–7** owa\_pattern.match function

Properties	Definitions
Parameters:	<p>line - the text to search in.</p> <p>mline - the text to search in. This is a owa_text.multi_line data type data type.</p> <p>pat - the pattern to match. This is either a VARCHAR2 or a owa_pattern.pattern data type data type. If it is a pattern, the output value of this parameter is the pattern matched.</p> <p>backrefs - the text that is matched. Each token that is matched is placed in a cell in the owa_text.vc_arr data type PL/SQL table. This parameter is a row_list that holds each string in the target that was matched by a sequence of tokens in the regular expression.</p> <p>rlist - an output parameter containing a list of matches.</p> <p>flags - whether or not the search is case-sensitive. If the value of this parameter is "i", the search is case-insensitive. Otherwise the search is case-sensitive.</p>
Returns:	TRUE if a match was found, FALSE otherwise.
Examples:	<p>KAZOO is the target where it is searching for the zoo.* regular expression. The period indicates any character other than newline, and the asterisk matches 0 or more of the preceding characters. In this case, it matches any character other than the newline.</p> <p>Therefore, this regular expression specifies that a matching target consists of zoo, followed by any set of characters neither ending in nor including a newline (which does not match the period). The i flag indicates to ignore case in the search. In this case, the function returns TRUE, which indicates that a match had been found.</p> <pre>boolean foundMatch; foundMatch := owa_pattern.match('KAZOO', 'zoo.*', 'i');</pre> <p>The following example searches for the string "goal" followed by any number of characters in <i>sometext</i>. If found,</p> <pre>sometext VARCHAR2(256); pat      VARCHAR2(256);  sometext := 'what is the goal?' pat := 'goal.*'; if owa_pattern.match(sometext, pat) then     http.print('Match found'); else     http.print('Match not found'); end if;</pre>

## 6.7 owa\_pattern.pattern data type

You can use a pattern as both an input and output parameter. Thus, you can pass the same regular expression to OWA\_PATTERN function calls, and it only has to be parsed once.

**Table 6–8** *owa\_pattern.pattern data type*

<b>Properties</b>	<b>Definitions</b>
Syntax:	owa_pattern.pattern - data type
Returns:	Not applicable.





---

---

# The owa\_sec Package

This chapter describes the functions, procedures, and data types in the `owa_sec` package in the PL/SQL Web Toolkit.

---

---

**Note:** Use the procedures and functions in the `owa_sec` package for custom authentication.

---

---

Parameters that have default values are optional.

## 7.1 Summary

`owa_sec.get_client_hostname` function - returns the client's hostname.

`owa_sec.get_client_ip` function - returns the client's IP address.

`owa_sec.get_password` function - returns the password that the user entered.

`owa_sec.get_user_id` function - returns the username that the user entered.

`owa_sec.set_authorization` procedure - enables the PL/SQL application to use custom authentication.

`owa_sec.set_protection_realm` procedure - defines the realm that the page is in.

## 7.2 `owa_sec.get_client_hostname` function

This function returns the hostname of the client.

**Table 7–1 owa\_sec.get\_client\_hostname function**

Properties	Definitions
Syntax:	<code>owa_sec.get_client_hostname return varchar2;</code>
Parameters:	None.
Returns:	The hostname.

## 7.3 owa\_sec.get\_client\_ip function

This function returns the IP address of the client.

**Table 7–2 owa\_sec.get\_client\_ip function**

Properties	Definitions
Syntax:	<code>owa_sec.get_client_ip return owa_util.ip_address;</code>
Parameters:	None.
Returns:	The IP address. The <code>owa_util.ip_address</code> data type is a PL/SQL table where the first four elements contain the four numbers of the IP address. For example, if the IP address is 123 . 45 . 67 . 89 and the variable <i>ipaddr</i> is of the <code>owa_util.ip_address</code> data type, the variable would contain the following values:  <code>ipaddr(1) = 123</code> <code>ipaddr(2) = 45</code> <code>ipaddr(3) = 67</code> <code>ipaddr(4) = 89</code>

## 7.4 owa\_sec.get\_password function

This function returns the password that the user used to log in. For security reasons, this function returns a true value only when custom authentication is used. If you call this function when you are not using custom authentication, the function returns an undefined value. Thus, the database passwords are not exposed.

**Table 7–3 owa\_sec.get\_password function**

Properties	Definitions
Syntax:	<code>owa_sec.get_password return varchar2;</code>
Parameters:	None.
Returns:	The password.

## 7.5 owa\_sec.get\_user\_id function

This function returns the username that the user used to log in.

**Table 7-4** *owa\_sec.get\_user\_id function*

Properties	Definitions
Syntax:	<code>owa_sec.get_user_id return varchar2;</code>
Parameters:	None.
Returns:	The username.

## 7.6 owa\_sec.set\_authorization procedure

This procedure, called in the initialization portion of the `owa_custom` package, sets the authorization scheme for the PL/SQL Gateway. This implements your `authorize` function, which authorizes the user before his requested procedure is run. The placement of the `authorize` function depends on the scheme you selected.

**Table 7–5 owa\_sec.set\_authorization procedure**

Properties	Definitions
Syntax:	<code>owa_sec.set_authorization(scheme in integer);</code>
Parameters:	<p>scheme - the authorization scheme. It is one of the following schemes for set_authorization:</p> <p>OWA_SEC.NO_CHECK - Specifies that the PL/SQL application is not to do any custom authentication. This is the default.</p> <p>OWA_SEC.GLOBAL - Defines an authorize function that is called for all users and all procedures. The function is <b>owa_custom.authorize</b> function in the "oas_public" schema.</p> <p>OWA_SEC.PER_PACKAGE - Define an authorize function that is called when procedures in a package or anonymous procedures are called. If the procedures are in a package, the <b>package.authorize</b> function in the user's schema is called to authorize the user. If the procedures are not in a package, then the anonymous authorize function in the user's schema is called.</p> <p>OWA_SEC.CUSTOM - Implements different authorize functions for each user. The function <b>owa_custom.authorize</b> in the user's schema is called to authorize the user. If the user's schema does not contain an <b>owa_custom.authorize</b> function, the PL/SQL Gateway looks for it in the "oas_public" schema.</p> <p>The custom authorize function has the following signature:</p> <pre>function authorize return boolean;</pre> <p>If the function returns TRUE, authentication succeeded. If it returns FALSE, authentication failed. If the authorize function is not defined, the Gateway returns an error and fails.</p>
Returns:	Not applicable

## 7.7 owa\_sec.set\_protection\_realm procedure

This procedure sets the realm of the page that is returned to the user. The user enters a username and login that already exist in the realm.

**Table 7–6 owa\_sec.set\_protection\_realm procedure**

Properties	Definitions
Syntax:	<code>owa_sec.set_protection_realm(realm in varchar2);</code>
Parameters:	realm - the realm where the page belongs. This string is displayed to the user.
Returns:	Not applicable.

---

---

## The owa\_text Package

The `owa_text` package contains subprograms used by `owa_pattern` for manipulating strings. They are externalized so you can use them directly.

### 8.1 Summary

`owa_text.add2multi` procedure - adds text to an existing `multi_line` type.

`owa_text.multi_line` data type - data type for holding large amounts of text.

`owa_text.new_row_list` - creates a new `row_list`.

`owa_text.print_multi` procedure - prints out the contents of a `multi_list`.

`owa_text.print_row_list` procedure - prints out the contents of a `row_list`.

`owa_text.row_list` data type - data type for holding data to be processed.

`owa_text.stream2multi` procedure - converts a `varchar2` to a `multi_line` type.

`owa_text.vc_arr` data type - data type for holding large amounts of text.

### 8.2 `owa_text.add2multi` procedure

This procedure adds content to an existing `owa_text.multi_line` data type.

**Table 8–1** owa\_text.add2multi procedure

Properties	Definitions
Syntax:	<pre>owa_text.add2multi(     stream      in      varchar2     mline       in out  multi_line     continue    in      boolean  DEFAULT TRUE);</pre>
Parameters:	<p>stream - the text to add.</p> <p>mline - the owa_text.multi_line data type. The output of this parameter contains <i>stream</i>.</p> <p>continue - if TRUE, the procedure appends <i>stream</i> within the previous final row (assuming it is less than 32K). If FALSE, the procedure places <i>stream</i> in a new row.</p>
Returns:	None.

## 8.3 owa\_text.multi\_line data type

This data type is a PL/SQL record that holds large amounts of text. The rows field, of type owa\_text.vc\_arr data type, contains the text data in the record.

**Table 8–2** owa\_text.multi\_line data type

Properties	Definitions
Syntax:	<pre>type multi_line is record (     rows          vc_arr,     num_rows      integer,     partial_row   boolean);</pre>
Returns:	Not applicable.

## 8.4 owa\_text.new\_row\_list

This function or procedure creates a new owa\_text.row\_list data type. The function version uses no parameters and returns a new empty row\_list. The procedure version creates the row\_list data type as an output parameter.

**Table 8–3** *owa\_text.new\_row\_list*

Properties	Definitions
Syntax:	<pre>/* procedure */ owa_text.new_row_list(rlist out row_list); /* function */ owa_text.new_row_list return row_list;</pre>
Parameters:	rlist - this is an output parameter containing the new row_list data type.
Returns:	The function version returns the new row_list data type.

## 8.5 owa\_text.print\_multi procedure

This procedure uses htp.print, htp.prn to print the "rows" field of the owa\_text.multi\_line data type.

**Table 8–4** *owa\_text.print\_multi procedure*

Properties	Definitions
Syntax:	<pre>owa_text.print_multi(mline in multi_line);</pre>
Parameters:	mline - the multi_line data type to print.
Returns:	The contents of the multi_line.

## 8.6 owa\_text.print\_row\_list procedure

This procedure uses htp.print, htp.prn to print the "rows" field of the owa\_text.row\_list data type.

**Table 8–5** *owa\_text.print\_row\_list procedure*

Properties	Definitions
Syntax:	<pre>owa_text.print_row_list(rlist in row_list);</pre>
Parameters:	rlist - the row_list data type to print.
Returns:	The contents of the row_list.

## 8.7 owa\_text.row\_list data type

This is the data type for holding data to be processed.

**Table 8–6** *owa\_text.row\_list data type*

Properties	Definitions
Syntax:	<pre>type row_list is record (     rows          int_arr,     num_rows      integer); int_arr is defined as: type int_arr is table of integer index by binary_integer;</pre>
Returns:	Not applicable.

## 8.8 owa\_text.stream2multi procedure

This procedure converts a string to a multi\_line data type.

**Table 8–7** *owa\_text.stream2multi procedure*

Properties	Definitions
Syntax:	<pre>owa_text.stream2multi(     stream  in  varchar2     mline   out multi_line);</pre>
Parameters:	stream - the string to convert. mline - the stream in owa_text.multi_line data type format.
Returns:	None.

## 8.9 owa\_text.vc\_arr data type

This is a component of the owa\_text.multi\_line data type.

**Table 8–8** *owa\_text.vc\_arr data type*

Properties	Definitions
Syntax:	type vc_arr is table of varchar2(32767) index by binary_integer;
Returns:	Not applicable.



---

---

## The owa\_util Package

The owa\_util package contains utility subprograms for performing operations such as getting the value of CGI environment variables, printing the data that is returned to the client, and printing the results of a query in an HTML table.

The owa\_util contains three types of utility subprograms.

- Dynamic SQL Utilities enable you to produce pages with dynamically generated SQL code.
- HTML utilities enable you to retrieve the values of CGI environment variables and perform URL redirects.
- Date utilities enable correct date-handling. Date values are simple strings in HTML, but are treated as a data type by the Oracle database.

### 9.1 Summary

owa\_util.bind\_variables function - prepares a SQL query and binds variables to it.

owa\_util.calendarprint procedure - prints a calendar.

owa\_util.cellsprint procedure - prints the contents of a query in an HTML table.

owa\_util.choose\_date procedure - generates HTML form elements that allow the user to select a date.

owa\_util.dateType data type - data type to hold date information.

owa\_util.get\_cgi\_env function - returns the value of the specified CGI environment variable.

owa\_util.get\_owa\_service\_path function - returns the full virtual path for the PL/SQL Gateway.

owa\_util.get\_procedure function - returns the name of the procedure that is invoked by the PL/SQL Gateway.

owa\_util.http\_header\_close procedure - closes the HTTP header.

owa\_util.ident\_arr data type - a data type

owa\_util.ip\_address data type - used by the owa\_sec.get\_client\_ip function.

owa\_util.listprint procedure - generates a HTML form element that contains data from a query.

owa\_util.mime\_header procedure - generates the Content-type line in the HTTP header.

owa\_util.print\_cgi\_env procedure - generates a list of all CGI environment variables and their values.

owa\_util.redirect\_url procedure - generates the Location line in the HTTP header.

owa\_util.showpage procedure - prints a page generated by the htp and htf packages in SQL\*Plus.

owa\_util.showsource procedure - prints the source for the specified subprogram.

owa\_util.signature procedure - prints a line that says that the page is generated by the PL/SQL Agent.

owa\_util.status\_line procedure - generates the Status line in the HTTP header.

owa\_util.tablePrint function - prints the data from a table in the database as an HTML table.

owa\_util.todate function - converts dateType data to the standard PL/SQL date type.

owa\_util.who\_called\_me procedure - returns information on the caller of the procedure.

## 9.2 owa\_util.bind\_variables function

This function prepares a SQL query by binding variables to it, and stores the output in an opened cursor. Use this function as a parameter to a procedure sending a dynamically generated query. Specify up to 25 bind variables.

**Table 9–1** *owa\_util.bind\_variables function*

Properties	Definitions
Syntax:	<pre> owa_util.bind_variables(     theQuery      in      varchar2  DEFAULT NULL     bv1Name       in      varchar2  DEFAULT NULL     bv1Value      in      varchar2  DEFAULT NULL     bv2Name       in      varchar2  DEFAULT NULL     bv2Value      in      varchar2  DEFAULT NULL     bv3Name       in      varchar2  DEFAULT NULL     bv3Value      in      varchar2  DEFAULT NULL     ...     bv25Name      in      varchar2  DEFAULT NULL     bv25Value     in      varchar2  DEFAULT NULL) return integer; </pre>
Parameters:	<p>theQuery - the SQL query statement. This must be a SELECT statement.</p> <p>bv1Name - the name of the variable.</p> <p>bv2Value - the value of the variable.</p>
Returns:	An integer identifying the opened cursor.

## 9.3 owa\_util.calendarprint procedure

This procedure creates a calendar in HTML. Each date in the calendar can contain any number of hypertext links. Design your query as follows:

- The first column is a DATE. This correlates the information produced by the query with the calendar output generated by the procedure.
- The query output must be sorted on this column using ORDER BY.
- The second column contains the text, if any, that you want printed for that date.
- The third column contains the destination for generated links. Each item in the second column becomes a hypertext link to the destination given in this column. If this column is omitted, the items in the second column are simple text, not links.

This procedure has 2 versions. Version 1 uses a hard-coded query stored in a varchar2 string. Version 2 uses a dynamic query prepared with the owa\_util.bind\_variables function.

**Table 9–2** owa\_util.calendarprint procedure

Properties	Definitions
Syntax:	<pre>owa_util.calendarprint(   p_query      in      varchar2   p_mf_only    in      varchar2  DEFAULT 'N');  owa_util.calendarprint(   p_cursor     in      integer   p_mf_only    in      varchar2  DEFAULT 'N');</pre>
Parameters:	<p><b>p_query</b> - a PL/SQL query. See the description above on what the query returns.</p> <p><b>p_cursor</b> - a PL/SQL cursor containing the same format as <i>p_query</i>.</p> <p><b>p_mf_only</b> - if "N" (the default), the generated calendar includes Sunday through Saturday. Otherwise, it includes Monday through Friday only.</p>
Generates:	A calendar in the form of an HTML table with a visible border.

## 9.4 owa\_util.cellsprint procedure

This procedure generates an HTML table from the output of a SQL query. SQL atomic data items are mapped to HTML cells and SQL rows to HTML rows. You must write the code to begin and end the HTML table. There are nine versions of this procedure:

- The first version passes the results of a query into an index table. Perform the query and cellsprint does the formatting. To have more control in generating an HTML table from the output of an SQL query, use the `htf.format_cell` function.
- The second and third versions display rows (up to the specified maximum) returned by the query or cursor.
- The fourth and fifth versions exclude a specified number of rows from the HTML table. Use the fourth and fifth versions to scroll through result sets by saving the last row seen in a hidden form element.

The sixth through ninth versions are the same as the first four versions, except that they return a row count output parameter.

**Table 9–3** *owa\_util.cellsprint procedure*

Properties	Definitions
Syntax:	<pre> owa_util.cellsprint(   p_colCnt      in    integer   p_resultTbl   in    vc_arr   p_format_numbers in  varchar2  DEFAULT NULL);  owa_util.cellsprint(   p_theQuery    in    varchar2   p_max_rows    in    number     DEFAULT 100   p_format_numbers in  varchar2  DEFAULT NULL);  owa_util.cellsprint(   p_theCursor   in    integer   p_max_rows    in    number     DEFAULT 100   p_format_numbers in  varchar2  DEFAULT NULL);  owa_util.cellsprint(   p_theQuery    in    varchar2   p_max_rows    in    number     DEFAULT 100   p_format_numbers in  varchar2  DEFAULT NULL   p_skip_rec    in    number     DEFAULT 0   p_more_data   out   boolean);  owa_util.cellsprint(   p_theCursor   in    integer   p_max_rows    in    number     DEFAULT 100   p_format_numbers in  varchar2  DEFAULT NULL   p_skip_rec    in    number     DEFAULT 0   p_more_data   out   boolean);  owa_util.cellsprint(   p_theQuery    in    varchar2   p_max_rows    in    number     DEFAULT 100   p_format_numbers in  varchar2  DEFAULT NULL   p_reccnt     out   number);  owa_util.cellsprint(   p_theCursor   in    integer   p_max_rows    in    number     DEFAULT 100   p_format_numbers in  varchar2  DEFAULT NULL   p_reccnt     out   number); </pre>

**Table 9–3** owa\_util.cellsprint procedure

Properties	Definitions
	<pre> owa_util.cellsprint(   p_theQuery      in   varchar2   p_max_rows      in   number      DEFAULT 100   p_format_numbers in   varchar2   DEFAULT NULL   p_skip_rec      in   number      DEFAULT 0   p_more_data     out   boolean   p_reccnt       out   number); </pre>
	<pre> owa_util.cellsprint(   p_theCursor     in   integer   p_max_rows      in   number      DEFAULT 100   p_format_numbers in   varchar2   DEFAULT NULL   p_skip_rec      in   number      DEFAULT 0   p_more_data     out   boolean   p_reccnt       out   number); </pre>
Parameters:	<p>p_colCnt - the number of columns in the table.</p> <p>p_theQuery - a SQL SELECT statement.</p> <p>p_theCursor - a cursor ID. This can be the return value from the owa_util.bind_variables function.</p> <p>p_max_rows - the maximum number of rows to print.</p> <p>p_format_numbers - if the value of this parameter is not NULL, number fields are right-justified and rounded to two decimal places.</p> <p>p_skip_rec - the number of rows to exclude from the HTML table.</p> <p>p_more_data - TRUE if there are more rows in the query or cursor, FALSE otherwise.</p> <p>p_reccnt - the number of rows that have been returned by the query. This value does not include skipped rows (if any).</p> <p>p_resultTbl - the index table which will contain the result of the query. Each entry in the query will correspond to one column value.</p>
Generates:	<pre> &lt;tr&gt;&lt;td&gt;QueryResultItem&lt;/td&gt;&lt;td&gt;QueryResultItem&lt;/td&gt;&lt;/tr&gt; &lt;tr&gt;&lt;td&gt;QueryResultItem&lt;/td&gt;&lt;td&gt;QueryResultItem&lt;/td&gt;&lt;/tr&gt; </pre>

## 9.5 owa\_util.choose\_date procedure

This procedure generates three HTML form elements that allow the user to select the day, the month, and the year. The parameter in the procedure that receives the data from these elements must be a owa\_util.dateType data type. Use the owa\_

util.todate function to convert the owa\_util.dateType data type value to the standard Oracle7 DATE data type.

**Table 9–4** owa\_util.choose\_date procedure

Properties	Definitions
Syntax:	<pre>owa_util.choose_date(     p_name      in      varchar2,     p_date      in      date      DEFAULT SYSDATE);</pre>
Parameters:	<p>p_name - the name of the form elements.</p> <p>p_date - the initial date that is selected when the HTML page is displayed.</p>
Generates:	<pre>&lt;SELECT NAME="p_name" SIZE="1"&gt; &lt;OPTION value="01"&gt;1 ... &lt;OPTION value="31"&gt;31 &lt;/SELECT&gt; - &lt;SELECT NAME="p_name" SIZE="1"&gt; &lt;OPTION value="01"&gt;JAN ... &lt;OPTION value="12"&gt;DEC &lt;/SELECT&gt; - &lt;SELECT NAME="p_name" SIZE="1"&gt; &lt;OPTION value="1992"&gt;1992 ... &lt;OPTION value="2002"&gt;2002 &lt;/SELECT&gt;</pre>

## 9.6 owa\_util.dateType data type

The owa\_util.todate function converts an item of this type to the type DATE, which is understood and properly handled as data by the database. The procedure owa\_util.choose\_date procedure enables the user to select the desired date.

**Table 9–5** owa\_util.dateType data type

Properties	Definitions
Syntax:	type dateType is table of varchar2(10) index by binary_integer;
Returns:	Not applicable.

## 9.7 owa\_util.get\_cgi\_env function

This function returns the value of the specified CGI environment variable. Although the WRB is not operated through CGI, many WRB cartridges, including the PL/SQL Gateway, can make use of CGI environment variables.

**Table 9–6** *owa\_util.get\_cgi\_env function*

Properties	Definitions
Syntax:	<code>owa_util.get_cgi_env(param_name in varchar2) return varchar2;</code>
Parameters:	<code>param_name</code> - the name of the CGI environment variable. It is case-insensitive. Get the values of all CGI environment variables except for <code>QUERY_STRING</code> because the PL/SQL Gateway parses the value of <code>QUERY_STRING</code> to determine the parameters to pass to the stored procedure.
Returns:	The value of the specified CGI environment variable. If the variable is not defined, the function returns <code>NULL</code> .

## 9.8 owa\_util.get\_owa\_service\_path function

This function returns the full virtual path of the PL/SQL Gateway that is handling the request.

**Table 9–7** *owa\_util.get\_owa\_service\_path function*

Properties	Definitions
Syntax:	<code>owa_util.get_owa_service_path return varchar2;</code>
Parameters:	None.
Returns:	A virtual path of the PL/SQL Gateway that is handling the request.

## 9.9 owa\_util.get\_procedure function

This function returns the name of the procedure that is being invoked by the PL/SQL Gateway.



**Table 9–8** *owa\_util.get\_procedure function*

Properties	Definitions
Syntax:	<code>owa_util.get_procedure return varchar2;</code>
Parameters:	None.
Returns:	The name of a procedure, including the package name if the procedure is defined in a package.

## 9.10 owa\_util.http\_header\_close procedure

This procedure generates a newline character to close the HTTP header. Use this procedure if you have not closed the header by using the *bclose\_header* parameter in calls such as `owa_util.mime_header` procedure, `owa_util.redirect_url` procedure, or `owa_util.status_line` procedure. The HTTP header must be closed before any `http.print` or `http.prn` calls.

**Table 9–9** *owa\_util.http\_header\_close procedure*

Properties	Definitions
Syntax:	<code>owa_util.http_header_close;</code>
Parameters:	None.
Generates:	A newline character, which closes the HTTP header.

## 9.11 owa\_util.ident\_arr data type

This data type is used for an array.

**Table 9–10** *owa\_util.ident\_arr data type*

Properties	Definitions
Syntax:	<code>type ident_arr is table of varchar2(30) index by binary_integer;</code>
Returns:	Not applicable.

## 9.12 owa\_util.ip\_address data type

This data type is used by the `owa_sec.get_client_ip` function.

**Table 9–11** *owa\_util.ip\_address data type*

Properties	Definitions
Syntax:	<code>type ip_address is table of integer index by binary_integer;</code>
Returns:	Not applicable.

## 9.13 owa\_util.listprint procedure

This procedure generates an HTML selection list form element from the output of a SQL query. The columns in the output of the query are handled in the following manner:

- The first column specifies the values that are sent back. These values are for the VALUE attribute of the OPTION tag.
- The second column specifies the values that the user sees.
- The third column specifies whether or not the row is marked as SELECTED in the OPTION tag. If the value is not NULL, the row is selected.

There are two versions of this procedure. The first version contains a hard-coded SQL query, and the second version uses a dynamic query prepared with the owa\_util.bind\_variables function.

**Table 9–12** *owa\_util.listprint procedure*

Properties	Definitions
Syntax:	<pre> owa_util.listprint(     p_theQuery    in      varchar2     p_cname       in      varchar2     p_nsize       in      number     p_multiple    in      boolean  DEFAULT FALSE);  owa_util.listprint(     p_theCursor   in      integer     p_cname       in      varchar2     p_nsize       in      number     p_multiple    in      boolean  DEFAULT FALSE); </pre>
Parameters:	<p><b>p_theQuery</b> - the SQL query.</p> <p><b>p_theCursor</b> - the cursor ID. This can be the return value from the <code>owa_util.bind_variables</code> function.</p> <p><b>p_cname</b> - the name of the HTML form element.</p> <p><b>p_nsize</b> - the size of the form element (this controls how many items the user can see without scrolling).</p> <p><b>p_multiple</b> - whether multiple selection is permitted.</p>
Generates:	<pre> &lt;SELECT NAME="p_cname" SIZE="p_nsize"&gt; &lt;OPTION SELECTED value='value_from_the_first_column'&gt;value_from_ the_second_column &lt;OPTION SELECTED value='value_from_the_first_column'&gt;value_from_ the_second_column . . . &lt;/SELECT&gt; </pre>

## 9.14 owa\_util.mime\_header procedure

This procedure changes the default MIME header that the script returns. This procedure must come before any `http.print` or `http.prn` calls to direct the script not to use the default MIME header.

**Table 9–13** *owa\_util.mime\_header procedure*

Properties	Definitions
Syntax:	<pre>owa_util.mime_header(     ccontent_type in      varchar2  DEFAULT 'text/html',     bclose_header in     boolean    DEFAULT TRUE,     ccharset          in   varchar2  DEFAULT NULL);</pre>
Parameters:	<p>ccontent_type - the MIME type to generate.</p> <p>bclose_header - whether or not to close the HTTP header. If TRUE, two newlines are sent, which closes the HTTP header. Otherwise, one newline is sent, and the HTTP header remains open.</p> <p>ccharset - the character set to use.</p>
Generates:	Content-type: <ccontent_type>; charset=<ccharset>
Example:	<pre>owa_util.mime_header('text/plain', false, 'ISO-8859-4') generates: Content-type: text/plain; charset=ISO-8859-4\n</pre>

## 9.15 owa\_util.print\_cgi\_env procedure

This procedure generates all the CGI environment variables and their values made available by the PL/SQL Gateway to the stored procedure.

**Table 9–14** *owa\_util.print\_cgi\_env procedure*

Properties	Definitions
Syntax:	owa_util.print_cgi_env;
Parameters:	None.
Generates:	<p>A list in the following format:</p> <pre>cgi_env_var_name = value\n</pre>

## 9.16 owa\_util.redirect\_url procedure

This procedure specifies that the application server is to visit the specified URL. The URL may specify either a web page to return or a program to execute. This procedure must come before any http or htf procedure or function call.

**Table 9–15** *owa\_util.redirect\_url procedure*

Properties	Definitions
Syntax:	<code>owa_util.redirect_url(     curl          in          varchar2     bclose_header in          boolean    DEFAULT TRUE);</code>
Parameters:	curl - the URL to visit.  bclose_header - whether or not to close the HTTP header. If TRUE, two newlines are sent, which closes the HTTP header. Otherwise, one newline is sent, and the HTTP header is still open.
Generates:	Location: <code>&lt;curl&gt;\n\n</code>

## 9.17 owa\_util.showpage procedure

This procedure prints out the HTML output of a procedure in SQL\*Plus, SQL\*DBA, or Oracle Server Manager. The procedure must use the `htp` or `htf` packages to generate the HTML page, and this procedure must be issued after the procedure has been called and before any other HTP or HTF subprograms are directly or indirectly called. This method is useful for generating pages filled with static data. This procedure uses **dbms\_output** and is limited to 255 characters per line and an overall buffer size of 1,000,000 bytes.

**Table 9–16** *owa\_util.showpage procedure*

Properties	Definitions
Syntax:	<code>owa_util.showpage;</code>
Parameters:	None.
Generates:	The output of <code>htp</code> procedure is displayed in SQL*Plus, SQL*DBA, or Oracle Server Manager. For example:  <pre>SQL&gt; set serveroutput on SQL&gt; spool gretzky.html SQL&gt; execute hockey.pass("Gretzky") SQL&gt; execute owa_util.showpage SQL&gt; exit</pre> <p>This would generate an HTML page that could be accessed from Web browsers.</p>

## 9.18 owa\_util.showsource procedure

This procedure prints the source of the specified procedure, function, or package. If a procedure or function which belongs to a package is specified, then the entire package is displayed.

**Table 9–17** *owa\_util.showsource procedure*

Properties	Definitions
Syntax:	<code>owa_util.showsource (cname in varchar2);</code>
Parameters:	cname - name of the procedure or function.
Generates:	The source code of the specified function, procedure, or package.

## 9.19 owa\_util.signature procedure

This procedure generates an HTML line followed by a signature line on the HTML document. If a parameter is specified, the procedure also generates a hypertext link to view the PL/SQL source for that procedure. The link calls the owa\_util.showsource procedure.

**Table 9–18** *owa\_util.signature procedure*

Properties	Definitions
Syntax:	<code>owa_util.signature;</code> <code>owa_util.signature (cname in varchar2);</code>
Parameters:	cname - the function or procedure whose source you want to show.
Generates:	Without a parameter, the procedure generates a line that looks like the following:  This page was produced by the <b>PL/SQL Agent</b> on August 9, 2001 09:30.  With a parameter, the procedure generates a signature line in the HTML document that looks like the following:  This page was produced by the <b>PL/SQL Agent</b> on 8/09/01 09:30 <a href="#">View PL/SQL Source</a>

## 9.20 owa\_util.status\_line procedure

This procedure sends a standard HTTP status code to the client. This procedure must come before any `http.print` or `http.prn` calls so that the status code is returned as part of the header, rather than as "content data".

**Table 9–19** *owa\_util.status\_line procedure*

Properties	Definitions
Syntax:	<pre>owa_util.status_line(     nstatus      in      integer,     creason      in      varchar2  DEFAULT NULL     bclose_header in      boolean  DEFAULT TRUE);</pre>
Parameters:	<p>nstatus - the status code.</p> <p>creason - the string for the status code.</p> <p>bclose_header - whether or not to close the HTTP header. If TRUE, two newlines are sent, which closes the HTTP header. Otherwise, one newline is sent, and the HTTP header is still open.</p>
Generates:	Status: <nstatus> <creason>\n\n

## 9.21 owa\_util.tablePrint function

This function generates either preformatted tables or HTML tables (depending on the capabilities of the user's browser) from database tables. RAW columns are supported, but LONG RAW columns are not. References to LONG RAW columns will print the result 'Not Printable'. In this function, *attributes* is the second, rather than the last, parameter.

**Table 9–20** owa\_util.tablePrint function

Properties	Definitions
Syntax:	<pre>owa_util.tablePrint(   ctable          in          varchar2   cattributes     in          varchar2  DEFAULT NULL   ntable_type     in          integer    DEFAULT HTML_TABLE   ccolumns        in          varchar2  DEFAULT '*'   cclauses        in          varchar2  DEFAULT NULL   ccol_aliases    in          varchar2  DEFAULT NULL   nrow_min        in          number    DEFAULT 0   nrow_max        in          number    DEFAULT NULL) return boolean;</pre>
Parameters:	<p><b>ctable</b> - the database table.</p> <p><b>cattributes</b> - other attributes to be included as-is in the tag.</p> <p><b>ntable_type</b> - how to generate the table. Specify "HTML_TABLE" to generate the table using &lt;TABLE&gt; tags or "PRE_TABLE" to generate the table using the &lt;PRE&gt; tags.</p> <p><b>ccolumns</b> - a comma-delimited list of columns from <i>ctable</i> to include in the generated table.</p> <p><b>cclauses</b> - WHERE or ORDER BY clauses, which specify which rows to retrieve from the database table, and how to order them.</p> <p><b>ccol_aliases</b> - a comma-delimited list of headings for the generated table.</p> <p><b>nrow_min</b> - the first row, of those retrieved, to display.</p> <p><b>nrow_max</b> - the last row, of those retrieved, to display.</p>
Generates:	A preformatted or HTML table. Returns TRUE if there are more rows beyond the nrow_max requested, FALSE otherwise.



**Table 9–20** owa\_util.tablePrint function

Properties	Definitions
------------	-------------

**Examples:** For browsers that do not support HTML tables, create the following procedure:

```
create or replace procedure showemps is
  ignore_more boolean;
begin
  ignore_more := owa_util.tablePrint('emp', 'BORDER', OWA_UTIL.PRE_
TABLE);
end;
```

Requesting a URL such as: <http://myhost:8080/ows-bin/hr/plsql/showemps> returns to the following to the client:

<PRE>

```
-----
| EMPNO | ENAME | JOB          | MGR | HIREDATE   | SAL | COMM | DEPTNO |
-----|-----|-----|-----|-----|-----|-----|-----|
| 7369 | SMITH | CLERK       | 7902 | 17-DEC-80 | 800 |      | 20 |
| 7499 | ALLEN | SALESMAN    | 7698 | 20-FEB-81 | 1600 | 300 | 30 |
| 7521 | WARD  | SALESMAN    | 7698 | 22-FEB-81 | 1250 | 500 | 30 |
| 7566 | JONES | MANAGER     | 7839 | 02-APR-81 | 2975 |      | 20 |
| 7654 | MARTIN | SALESMAN    | 7698 | 28-SEP-81 | 1250 | 1400 | 30 |
| 7698 | BLAKE | MANAGER     | 7839 | 01-MAY-81 | 2850 |      | 30 |
| 7782 | CLARK | MANAGER     | 7839 | 09-JUN-81 | 2450 |      | 10 |
| 7788 | SCOTT | ANALYST     | 7566 | 09-DEC-82 | 3000 |      | 20 |
| 7839 | KING  | PRESIDENT   |      | 17-NOV-81 | 5000 |      | 10 |
| 7844 | TURNER | SALESMAN    | 7698 | 08-SEP-81 | 1500 | 0    | 30 |
| 7876 | ADAMS | CLERK       | 7788 | 12-JAN-83 | 1100 |      | 20 |
| 7900 | JAMES | CLERK       | 7698 | 03-DEC-81 | 950  |      | 30 |
| 7902 | FORD  | ANALYST     | 7566 | 03-DEC-81 | 3000 |      | 20 |
| 7934 | MILLER | CLERK       | 7782 | 23-JAN-82 | 1300 |      | 10 |
-----
```

</PRE>

To view the employees in department 10, and only their employee ids, names, and salaries, create the following procedure:

```
create or replace procedure showemps_10 is
  ignore_more boolean;
begin
  ignore_more := owa_util.tablePrint
('EMP', 'BORDER', OWA_UTIL.PRE_TABLE,
'empno, ename, sal',
'where deptno=10 order by empno',
'Employee Number, Name, Salary');
end;
```

**Table 9–20** owa\_util.tablePrint function

Properties	Definitions
------------	-------------

A request for a URL like **http://myhost:8080/ows-bin/hr/plsql/showemps\_10** would return the following to the client:

```
<PRE>
-----
| Employee Number |Name| Salary |
-----
| 7782| CLARK| 2450 |
| 7839| KING | 5000 |
| 7934| MILLER | 1300 |
-----
</PRE>
```

For browsers that support HTML tables, to view the department table in an HTML table, create the following procedure:

```
create or replace procedure showdept is
  ignore_more boolean;
begin
  ignore_more := owa_util.tablePrint('dept', 'BORDER');
end;
```

**Table 9–20** *owa\_util.tablePrint* function

Properties	Definitions
	<p>A request for a URL like <b>http://myhost:8080/ows-bin/hr/plsql/showdept</b> would return the following to the client:</p> <pre> &lt;TABLE BORDER&gt; &lt;TR&gt; &lt;TH&gt;DEPTNO&lt;/TH&gt; &lt;TH&gt;DNAME&lt;/TH&gt; &lt;TH&gt;LOC&lt;/TH&gt; &lt;/TR&gt; &lt;TR&gt; &lt;TD ALIGN="LEFT"&gt;10&lt;/TD&gt; &lt;TD ALIGN="LEFT"&gt;ACCOUNTING&lt;/TD&gt; &lt;TD ALIGN="LEFT"&gt;NEW YORK&lt;/TD&gt; &lt;/TR&gt; &lt;TR&gt; &lt;TD ALIGN="LEFT"&gt;20&lt;/TD&gt; &lt;TD ALIGN="LEFT"&gt;RESEARCH&lt;/TD&gt; &lt;TD ALIGN="LEFT"&gt;DALLAS&lt;/TD&gt; &lt;/TR&gt; &lt;TR&gt; &lt;TD ALIGN="LEFT"&gt;30&lt;/TD&gt; &lt;TD ALIGN="LEFT"&gt;SALES&lt;/TD&gt; &lt;TD ALIGN="LEFT"&gt;CHICAGO&lt;/TD&gt; &lt;/TR&gt; &lt;TR&gt; &lt;TD ALIGN="LEFT"&gt;40&lt;/TD&gt; &lt;TD ALIGN="LEFT"&gt;OPERATIONS&lt;/TD&gt; &lt;TD ALIGN="LEFT"&gt;BOSTON&lt;/TD&gt; &lt;/TR&gt; &lt;/TABLE&gt; </pre>

A Web browser would formatn this to look like the following table:

DEPTNO	DNAME	LOC
10	ACCOUNTING	NEW YORK
20	RESEARCH	DALLAS
30	SALES	CHICAGO

## 9.22 owa\_util.todate function

This function converts the `owa_util.dateType` data type to the standard Oracle database `DATE` type.

**Table 9–21** *owa\_util.todate function*

Properties	Definitions
Syntax:	<code>owa_util.todate(p_dateArray in dateType) return date;</code>
Parameters:	<code>p_dateArray</code> - the value to convert.
Generates	A standard <code>DATE</code> .

## 9.23 owa\_util.who\_called\_me procedure

This procedure returns information (in the form of output parameters) about the PL/SQL code unit that invoked it.

**Table 9–22** *owa\_util.who\_called\_me procedure*

Properties	Definitions
Syntax:	<pre> owa_util.who_called_me(     owner          out          varchar2     name           out          varchar2     lineno         out          number     caller_t       out          varchar2); </pre>
Parameters:	<p><code>owner</code> - the owner of the program unit.</p> <p><code>name</code> - the name of the program unit. This is the name of the package, if the calling program unit is wrapped in a package, and the name of the procedure or function if the calling program unit is a stand-alone procedure or function. If the calling program unit is part of an anonymous block, this is <code>NULL</code>.</p> <p><code>lineno</code> - the line number within the program unit where the call was made.</p> <p><code>caller_t</code> - the type of program unit that made the call. The possibilities are: package body, anonymous block, procedure, and function. Procedure and function are only for stand-alone procedures and functions.</p>
Generates	Not applicable.

---

---

# Index

## A

---

address tag, 1-6, 6-4  
anchor, 1-6  
applet tags, 1-2, 1-7  
area tag, 1-8

## B

---

base tag, 1-9  
basefront tag, 1-10  
bgsound tag, 1-10  
big tag, 1-10  
blockquote tag  
    closed, 1-11  
    open, 1-11  
body tag, 1-11  
bold tag, 1-12

## C

---

cache, 2-1  
center tag  
    tags  
        center, 1-12  
centerclose tag, 1-13  
centeropen tag, 1-13  
CGI environment variables, 9-8, 9-12  
character formatting tags (PL/SQL cartridge), 1-4  
checkbox form, 1-21  
cite tag, 1-13  
code tag, 1-14  
comments in HTML, 1-14

## D

---

database  
    locking, 5-1  
dfn tag, 1-15  
dirlistclose tag, 1-15  
dirlistopen tag, 1-15  
div tag, 1-15  
dlistDef tag, 1-16  
dlistTerm tag, 1-17  
download\_file, 1-17

## E

---

emphasis tag, 1-18  
environment variables  
    retrieving in the PL/SQL Cartridge, 9-8  
escape\_sc, 1-19  
escape\_url, 1-19  
etag, 2-3  
expires caching, 2-2

## F

---

fontClose tag, 1-20  
fontOpen tag, 1-20  
fonts  
    big, 1-10  
form tags, 1-3  
formCheckbox, 1-21  
formClose tag, 1-22  
formFile, 1-22  
formHidden, 1-23  
formImage, 1-23

- formOpen tag, 1-22
- formPassword, 1-24
- formRadio, 1-25
- formReset, 1-26
- formSelectClose, 1-26
- formSelectOpen, 1-26
- formSelectOption, 1-27
- formSubmit, 1-28
- formText, 1-29
- formTextarea, 1-29
- formTextarea2, 1-29
- frame tag, 1-31
- frame tags, 1-5
- framesetClose, 1-32

## G

---

- get\_download\_files\_list, 1-18

## H

---

- head tag, 1-33
- heading tag, 1-33
- HTML comment, 1-14
- htmlClose tag, 1-34
- htmlOpen tag, 1-34
- htp.address, 1-6, 6-4
- htp.anchor, 1-6
- htp.anchor2, 1-6
- htp.appletclose, 1-7
- htp.appletopen, 1-7
- htp.area, 1-8
- htp.base, 1-9
- htp.basefont, 1-10
- htp.bg sound, 1-10
- htp.big, 1-10
- htp.blockquoteClose, 1-11
- htp.blockquoteOpen, 1-11
- htp.bodyClose, 1-11
- htp.bold, 1-12
- htp.br, 1-43
- htp.center, 1-12
- htp.centerClose, 1-13
- htp.centerOpen, 1-13
- htp.cite, 1-13
- htp.code, 1-14
- htp.comment, 1-14
- htp.dfn, 1-15
- htp.dirlistClose, 1-15
- htp.dirlistOpen, 1-15
- htp.div, 1-15
- htp.dlistClose, 1-16
- htp.dlistDef, 1-16
- htp.dlistOpen, 1-16
- htp.dlistTerm, 1-17
- htp.em, 1-18
- htp.emphasis, 1-18
- htp.fontClose, 1-20
- htp.fontOpen, 1-20
- htp.formCheckbox, 1-21
- htp.formClose, 1-22
- htp.formFile, 1-22
- htp.formHidden, 1-23
- htp.formImage, 1-23
- htp.formOpen, 1-22
- htp.formPassword, 1-24
- htp.formRadio, 1-25
- htp.formReset, 1-26
- htp.formSelectClose, 1-26
- htp.formSelectOpen, 1-26
- htp.formSelectOption, 1-27
- htp.formSubmit, 1-28
- htp.formText, 1-29
- htp.formTextarea, 1-29
- htp.formTextareaClose, 1-30
- htp.frame, 1-31
- htp.framesetClose, 1-32
- htp.framesetOpen, 1-32
- htp.headClose, 1-33
- htp.header, 1-33
- htp.headOpen, 1-33
- htp.hr, 1-37
- htp.htmlClose, 1-34
- htp.htmlOpen, 1-34
- htp.img, 1-35
- htp.img2, 1-35
- htp.isindex, 1-36
- htp.italic, 1-36
- htp.kbd, 1-36
- htp.keyboard, 1-36

htp.line, 1-37  
htp.linkRel, 1-38  
htp.linkRev, 1-38  
htp.listHeader, 1-39  
htp.listingClose, 1-39  
htp.listingOpen, 1-39  
htp.listItem, 1-39  
htp.mailClose, 1-41  
htp.mailto, 1-40  
htp.mapOpen, 1-41  
htp.menulistClose, 1-41  
htp.menulistOpen, 1-41  
htp.meta, 1-42  
htp.nl, 1-43  
htp.nobr, 1-43  
htp.noframesClose, 1-43  
htp.noframesOpen, 1-43  
htp.olistClose, 1-44  
htp.olistOpen, 1-44  
htp.para, 1-45  
htp.paragraph, 1-45  
htp.param, 1-45  
htp.plaintext, 1-46  
htp.preClose, 1-46  
htp.preOpen, 1-46  
htp.print, 1-47  
htp.prints, 1-48  
htp.prn, 1-47  
htp.ps, 1-48  
htp.s, 1-48  
htp.sample, 1-49  
htp.script, 1-49  
htp.strike, 1-50  
htp.strong, 1-51  
htp.style, 1-51  
htp.sub, 1-52  
htp.sup, 1-52  
htp.tableCaption, 1-53  
htp.tableClose, 1-55  
htp.tableData, 1-53  
htp.tableHeader, 1-54  
htp.tableOpen, 1-55  
htp.tableRowClose, 1-56  
htp.tableRowOpen, 1-56  
htp.teletype, 1-57

htp.textareaOpen, 1-30  
htp.textareaOpen2, 1-30  
htp.title, 1-58  
htp.ulistClose, 1-58  
htp.ulistOpen, 1-58  
htp.underline, 1-59  
htp.variable, 1-59  
htp.wbr, 1-59

---

## I

img tag, 1-35  
IP address  
    retrieving in the PL/SQL cartridge, 7-2  
isindex, 1-36  
italic tag, 1-36

---

## J

Java applets  
    referencing, 1-7

---

## K

keyboard tag, 1-36

---

## L

line tag, 1-37  
link tag, 1-38  
list item tag, 1-39  
list tags, 1-2  
listHeader tag, 1-39  
listingClose tag, 1-39  
listingOpen tag, 1-39

---

## M

mailto tag, 1-40  
map tags, 1-41  
menu list tag, 1-41  
meta tag, 1-42

---

## N

new line tag, 1-43

no break tag, 1-43  
noframes tags, 1-43

## O

---

ordered list tag

tags

olist, 1-44

owa\_cache, 2-1

owa\_cache.disable, 2-2

owa\_cache.get\_etag, 2-3

owa\_cache.get\_level, 2-3

owa\_cache.set\_not\_modified, 2-3

owa\_cookie.cookie data type, 3-1

owa\_cookie.get function, 3-2

owa\_cookie.get\_all procedure, 3-2

owa\_cookie.remove procedure, 3-3

owa\_cookie.send procedure, 3-3

owa\_cookie.vc\_arr data type, 3-1

owa\_image.get\_x function, 4-2

owa\_image.get\_y function, 4-2

owa\_image.NULL\_POINT package variable, 4-1

owa\_image.point data type, 4-2

owa\_opt\_lock.checksum function, 5-2

owa\_opt\_lock.get\_rowid function, 5-3

owa\_opt\_lock.store\_values procedure, 5-3

owa\_opt\_lock.vcArray data type, 5-2

owa\_opt\_lock.verify\_values function, 5-4

owa\_pattern.amatch function, 6-3

owa\_pattern.change function and procedure, 6-5

owa\_pattern.getpat procedure, 6-7

owa\_pattern.match function, 6-8

owa\_pattern.pattern data type, 6-11

owa\_sec.get\_client\_hostname function, 7-1

owa\_sec.get\_client\_ip function, 7-2

owa\_sec.get\_password function, 7-2

owa\_sec.get\_user\_id function, 7-3

owa\_sec.set\_authorization procedure, 7-3

owa\_sec.set\_protection\_realm procedure, 7-4

owa\_text.add2multi procedure, 8-1

owa\_text.multi\_line data type, 8-2

owa\_text.new\_row\_list, 8-2

owa\_text.print\_multi procedure, 8-3

owa\_text.print\_row\_list procedure, 8-3

owa\_text.row\_list data type, 8-3

owa\_text.stream2multi procedure, 8-4

owa\_text.vc\_arr data type, 8-4

owa\_util.bind\_variables function, 9-2

owa\_util.calendarprint procedure, 9-3

owa\_util.cellsprint procedure, 9-4

owa\_util.choose\_date procedure, 9-6

owa\_util.dateType data type, 9-7

owa\_util.get\_cgi\_env function, 9-8

owa\_util.get\_owa\_service\_path function, 9-8

owa\_util.get\_procedure function, 9-8

owa\_util.http\_header\_close procedure, 9-9

owa\_util.ident\_arr data type, 9-9

owa\_util.ip\_address data type, 9-9

owa\_util.listprint procedure, 9-10

owa\_util.mime\_header procedure, 9-11

owa\_util.print\_cgi\_env procedure, 9-12

owa\_util.redirect\_url procedure, 9-12

owa\_util.showpage procedure, 9-13

owa\_util.showsource procedure, 9-14

owa\_util.signature procedure, 9-14

owa\_util.status\_line procedure, 9-14

owa\_util.tablePrint function, 9-15

owa\_util.todate function, 9-20

owa\_util.who\_called\_me procedure, 9-20

## P

---

p\_expires, 2-2

paragraph formatting tags (PL/SQL cartridge), 1-4

paragraph tag, 1-45

parameter tag, 1-45

plaintext tag, 1-46

PL/SQL cartridge

applet tags, 1-2

character formatting tags, 1-4

form tags, 1-3

frame tags, 1-5

list tags, 1-2

paragraph formatting tags, 1-4

subprograms summary, 1-2

table tags, 1-3

PL/SQL Web Toolkit

htf package, 1-1

htp package, 1-1

owa\_cookie package, 3-1



- owa\_image package, 4-1
- owa\_opt\_lock package, 5-1
- owa\_pattern package, 6-1
- owa\_sec package, 7-1
- owa\_text package, 8-1
- owa\_util package, 9-1
- preformatted text tag, 1-46
- print tag, 1-47

## R

---

- regular expressions, 6-2
- revision tag, 1-38

## S

---

- sample tag, 1-49
- script tag, 1-49
- strike tag, 1-50
- strings
  - regular expressions, 6-2
- strong tag, 1-51
- style tag, 1-51
- subscript tag, 1-52
- superscript tag, 1-52

## T

---

- table tags (PL/SQL cartridge), 1-3
- tableCaption tag, 1-53
- tableClose tag, 1-55
- tableData tag, 1-53
- tableHeader tag, 1-54
- tableOpen tag, 1-55
- tableRowClose tag, 1-56
- tags
  - address, 1-6, 6-4
  - applet, 1-7
  - area, 1-8
  - base, 1-9
  - basefont, 1-10
  - bgsound, 1-10
  - big, 1-10
  - blockquote
    - closed, 1-11

- open, 1-11
- body, 1-11
- bold, 1-12
- centerclose, 1-13
- centeropen, 1-13
- cite, 1-13
- code, 1-14
- dfn, 1-15
- dirlistclose, 1-15
- dirlistopen, 1-15
- div, 1-15
- dlistDef, 1-16
- dlistTerm, 1-17
- emphasis, 1-18
- fontClose, 1-20
- fontOpen, 1-20
- formClose, 1-22
- formOpen, 1-22
- frame, 1-31
- head, 1-33
- header, 1-33
- htmlClose, 1-34
- htmlOpen, 1-34
- img, 1-35
- italic, 1-36
- keyboard, 1-36
- line, 1-37
- link, 1-38
- listHeader, 1-39
- listitem, 1-39
- mapClose, 1-41
- mapOpen, 1-41
- menulistClose, 1-41
- menulistOpen, 1-41
- meta, 1-42
- nl, 1-43
- nobr, 1-43
- noframes, 1-43
- paragraph, 1-45
- parameter, 1-45
- plaintext, 1-46
- pre, 1-46
- print, 1-47
- revision, 1-38
- sample, 1-49

- script, 1-49
- strike, 1-50
- strong, 1-51
- style, 1-51
- sub, 1-52
- sup, 1-52
- tableCaption, 1-53
- tableData, 1-53
- tableHeader, 1-54
- teletype, 1-57
- title, 1-58
- underline, 1-59
- unordered list, 1-58
- variable, 1-59
- wbr, 1-59

teletype tag, 1-57

title tag, 1-58

## **U**

---

- underline tag, 1-59
- unordered list tag, 1-58

## **V**

---

- validation caching, 2-1
- variable tag, 1-59
- vc\_arr data type, 3-1

## **W**

---

- wbr tag, 1-59